

# DBO17W2P500G30LF

#### DBO17W2P500G30LF Information

Heisener.com	DBO17W2P500G30LF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 17POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## DBO17W2P500G30LF Specifications

Manufacturer Amphenol FCI   Connectors, Interconnects D-Stub Connectors   Package -   Series DSub Connectors   Connector Style DSub Combod   Connector Style DSub Combod   Connector Style Pilg, Male Pins   Number of Positions 17 (15 + 2 Power)   Shell Size, Connector Layout 3 (DB, B) - 17W2   Contact Type Signal and Power   Contact Type Signal and Power   Flange Feature Board Side (4-40)   Flange Feature Solder   Flange Feature Solder   Found Infinish Sidel Concuring Indents, Mounting Brackets   Shell Material, Finish Stell, Tin Plated   Contact Finish Thickness -   Contact Finish Thickness -		
Connectors, Interconnects   D-Sub Connectors   Package   -   Series   DSub, Combo   Connector Style   D-Sub, Combo   Connector Type   Plug, Male Pins   Number of Positions   17 (15 + 2 Power)   Shell Size, Connector Layout   3 (DB, B) - 17W2   Contact Type   Signal and Power   Contact Type   Board Side (4-40)   Permination   Solder   Features   Board Lock, Grounding Indents, Mounting Brackets   Shell Material, Finish   Contact Finish Thickness   -   Shell Material Flammability Rating	Manufacturer Part Number	DBO17W2P500G30LF
D-Sub ConnectorsPackage-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Angress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FeaturesSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Series	DW
Number of Positions17 (15 + 2 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B) - 17W2Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	17 (15 + 2 Power)
Contact TypeSignal and PowerMounting TypeThrough Hole, Right AngleFange FeaturesBoard Side (4-40)FeaturesSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B) - 17W2
Flange FeatureBoard Side (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal and Power
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	-
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### DBO17W2P500G30LF Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DBO17W2P500G30LF Payment Methods





If you have any question about DBO17W2P500G30LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com