



DBR72410S Information



For Reference Only

Part NumberDBR72410SManufacturerCynergy 3CategoryRelays

Power Relays, Over 2 Amps

Description RELAY REED SPST-NC 3A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DBR72410S Specifications

Manufacturer Part Number Manufacturer Cynergy 3 Relays Power Relays, Over 2 Amps Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 25.9mA Coil Voltage Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Ams Release Time Mounting Type Chassis Mount Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 25.9mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	DBR72410S
Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 25.9mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	Cynergy 3
Package - Series D Relay Type Reed Coil Type Non Latching Coil Current 25.9mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesDRelay TypeReedCoil TypeNon LatchingCoil Current25.9mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time2msRelease Time3msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25.9mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time2msRelease Time3msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current25.9mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)3ASwitching Voltage1000VAC, 1000VDC - MaxTurn On Voltage (Max)20 VDCTurn Off Voltage (Min)4 VDCOperate Time2msRelease Time3msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Series	D
Coil Current 25.9mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	Reed
Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NC (1 Form B) Contact Rating (Current) 3A Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Current	25.9mA
Contact Rating (Current) Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VDC
Switching Voltage 1000VAC, 1000VDC - Max Turn On Voltage (Max) 20 VDC Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NC (1 Form B)
Turn On Voltage (Max) Turn Off Voltage (Min) 4 VDC Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style 20 VDC 4 VDC Cms A	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Switching Voltage	1000VAC, 1000VDC - Max
Operate Time 2ms Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	20 VDC
Release Time 3ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	4 VDC
Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	2ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	3ms
Termination Style Quick Connect - 0.250" (6.3mm)	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

DBR72410S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DBR72410S Payment Methods


































If you have any question about DBR72410S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com