



### DCH2-050US-0001 Information





For Reference Only

Part Number DCH2-050US-0001

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 6.5V 2W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DCH2-050US-0001 Specifications

Manufacturer Part Number         DCH2-050US-0001           Manufacturer         Artesyn Embedded Technologies           Category         Power Supplies - External/Internal (Off-Board)           Reckage         -           Series         DCH2           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6.5 V           Current - Output (Max)         300mA           Power (Watts)         2W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         0°C ~ 50°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         DCH2           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6.5V           Current - Output (Max)         300mA           Power (Watts)         2W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         0°C ~ 50°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Manufacturer Part Number	DCH2-050US-0001
Package-SeriesDCH2Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output6.5VCurrent - Output (Max)300mAPower (Watts)2WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature0°C ~ 50°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Manufacturer	Artesyn Embedded Technologies
Package         -           Series         DCH2           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6.5V           Current - Output (Max)         300mA           Power (Watts)         2W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         0°C ~ 50°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesDCH2Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output6.5VCurrent - Output (Max)300mAPower (Watts)2WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature0°C ~ 50°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $6.5\text{V}$ Current - Output (Max) $300\text{mA}$ Power (Watts) $2\text{W}$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.5\text{mm}$ I.D. $\times 5.5\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension $1.50^{\circ}$ L $\times 1.50^{\circ}$ W $\times 1.75^{\circ}$ H ( $38.1\text{mm} \times 38.1\text{mm} \times 44.4\text{mm}$ )	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 6.5V Current - Output (Max) 300mA Power (Watts) 2W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Series	DCH2
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 6.5V  Current - Output (Max) 300mA  Power (Watts) 2W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature 0°C ~ 50°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  6.5 V  Current - Output (Max)  300mA  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 50°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Form	Wall Mount
Voltage - Output  Current - Output (Max)  300mA  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 50°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  2W  No Load Power Consumption  - Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 50°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 50°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Voltage - Output	6.5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature $0^{\circ}$ C ~ $50^{\circ}$ COutput ConnectorBarrel Plug R/A, $2.5$ mm I.D. $x 5.5$ mm O.D. $x 9.5$ mmSize / Dimension $1.50^{\circ}$ L $x 1.50^{\circ}$ W $x 1.75^{\circ}$ H ( $38.1$ mm $x 38.1$ mm $x 44.4$ mm)	Current - Output (Max)	300mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $1.50^{\circ}\text{L} \times 1.50^{\circ}\text{W} \times 1.75^{\circ}\text{H} (38.1\text{mm} \times 38.1\text{mm} \times 44.4\text{mm})$	Power (Watts)	2W
Applications ITE (Commercial)  Efficiency - Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $1.50^{\circ}\text{L} \times 1.50^{\circ}\text{W} \times 1.75^{\circ}\text{H} (38.1\text{mm} \times 38.1\text{mm} \times 44.4\text{mm})$	No Load Power Consumption	-
Efficiency - Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $1.50^{\circ}\text{L} \times 1.50^{\circ}\text{W} \times 1.75^{\circ}\text{H} (38.1\text{mm} \times 38.1\text{mm} \times 44.4\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $1.50^{\circ}\text{L x }1.50^{\circ}\text{W x }1.75^{\circ}\text{H }(38.1\text{mm x }38.1\text{mm x }44.4\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Efficiency	-
Size / Dimension 1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)	Operating Temperature	0°C ~ 50°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	1.50" L x 1.50" W x 1.75" H (38.1mm x 38.1mm x 44.4mm)
		Report errors?

#### DCH2-050US-0001 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DCH2-050US-0001 Payment Methods



















### DCH2-050US-0001 Shipping Methods













If you have any question about DCH2-050US-0001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com