



#### DCH3-050US-0002 Information



For Reference Only

Part Number DCH3-050US-0002

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 3W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DCH3-050US-0002 Specifications

Manufacturer Part NumberDCH3-050US-0002ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesDCH3Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)550mAPower (Watts)2.8WNo Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 50°COutput ConnectorUSB MicroSize / Dimension2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         DCH3           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         550mA           Power (Watts)         2.8W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 50°C           Output Connector         USB Micro           Size / Dimension         2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Manufacturer Part Number	DCH3-050US-0002	
Package         -           Series         DCH3           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         550mA           Power (Watts)         2.8W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 50°C           Output Connector         USB Micro           Size / Dimension         2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Manufacturer	Artesyn Embedded Technologies	
Package         -           Series         DCH3           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         550mA           Power (Watts)         2.8W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 50°C           Output Connector         USB Micro           Size / Dimension         2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesDCH3Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)550mAPower (Watts)2.8WNo Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 50°COutput ConnectorUSB MicroSize / Dimension2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)		AC DC Desktop, Wall Adapters	
Region Utilized  North America  Form  Wall Mount  Input Type Fixed Blade  Voltage - Input 100 ~ 240 VAC  Voltage - Output 5V  Current - Output (Max) 550mA  Power (Watts)  No Load Power Consumption - Polarization -Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature 0°C ~ 50°C  Output Connector Size / Dimension  North America North America North America  North America  North America  North America  Pixel Blade  100 ~ 240 VAC   5V  Current - Output (Max)  550mA	Package	-	
FormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $550\text{mA}$ Power (Watts) $2.8W$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output ConnectorUSB MicroSize / Dimension $2.28^{\circ}\text{ L} \times 1.03^{\circ}\text{ W} \times 1.79^{\circ}\text{ H} (58.0 \text{mm} \times 26.1 \text{mm} \times 45.4 \text{mm})$	Series	DCH3	
Input Type  Fixed Blade  Voltage - Input  100 ~ 240 VAC  Voltage - Output  5V  Current - Output (Max)  Power (Watts)  100 ~ 240 VAC  550mA  2.8W  No Load Power Consumption  Polarization	Region Utilized	North America	
Voltage - Input  100 ~ 240 VAC  Voltage - Output  5V  Current - Output (Max)  550mA  Power (Watts)  2.8W  No Load Power Consumption  - Polarization  - Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 50°C  Output Connector  USB Micro  Size / Dimension  100 ~ 240 VAC  5V  Current - Output (Max)  5V  Current - Output (Max)  550mA  - C. Residual Commercial  100 ~ 240 VAC  5V  Current - Output (Max)  550mA  - C. Residual Commercial  100 ~ 240 VAC  50 C  100 C	Form	Wall Mount	
Voltage - Output  Current - Output (Max)  550mA  Power (Watts)  2.8W  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  Level IV  Operating Temperature  0°C ~ 50°C  Output Connector  USB Micro  Size / Dimension  5V  2.8W  TE (Commercial)  Level IV  0°C ~ 50°C  USB Micro  2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Input Type	Fixed Blade	
Current - Output (Max)  550mA  2.8W  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  Level IV  Operating Temperature  0°C ~ 50°C  Output Connector  USB Micro  Size / Dimension  550mA  2.8W  Commandary  - Commandary	Voltage - Input	100 ~ 240 VAC	
Power (Watts)  2.8W  No Load Power Consumption	Voltage - Output	5V	
No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level IV  Operating Temperature  0°C ~ 50°C  Output Connector  USB Micro  Size / Dimension  2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Current - Output (Max)	550mA	
Polarization - Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature 0°C ~ 50°C  Output Connector USB Micro  Size / Dimension 2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Power (Watts)	2.8W	
Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector USB Micro  Size / Dimension 2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	No Load Power Consumption	-	
Efficiency Level IV  Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector USB Micro  Size / Dimension 2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Polarization	-	
Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector USB Micro Size / Dimension $2.28^{\circ}\text{L} \times 1.03^{\circ}\text{W} \times 1.79^{\circ}\text{H} (58.0 \text{mm} \times 26.1 \text{mm} \times 45.4 \text{mm})$	Applications	ITE (Commercial)	
Output Connector  Size / Dimension  USB Micro  2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Efficiency	Level IV	
Size / Dimension 2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	Operating Temperature	0°C ~ 50°C	
	Output Connector	USB Micro	
Papart arrors?	Size / Dimension	2.28" L x 1.03" W x 1.79" H (58.0mm x 26.1mm x 45.4mm)	
Report errors:		Report erro	rs?

#### DCH3-050US-0002 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DCH3-050US-0002 Payment Methods



















### DCH3-050US-0002 Shipping Methods













If you have any question about DCH3-050US-0002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com