

DCM8C8SNA222

DCM8C8SNA222 Information

Containance contention	 DCM8C8SNA222 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN DSUB RCPT 8POS PNL MNT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DCM8C8SNA222 Specifications

Anufacturer ITT Canon, LLC Category Connectors, Interconnects Package D-Sub Connectors Package - Series Combo D?, D*M Connector Style D-Sub, Combo Connector Type Receptacle, Female Sockets Number of Positions 8 (Coax) Number of Rows 1 Shell Size, Connector Layout 4 (DC, C) - 8W8 Contact Type Coax Mounting Type Panel Mount, Through Hole Flange Feature Solder Features Shell Material, Finish Contact Finish Steel, Yellow Chromate Plated Zinc Contact Finish Thickness Gold Contact Finish Thickness Solpin (1.27µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Shell Size, Connector Layout(DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesShell Stell, Yellow Chromate Plated ZincShell Material, FinishStell, Yellow Chromate Plated ZincContact Finish ThicknessSoljari (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DCM8C8SNA222
D-Sub ConnectorsPackage-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Flange FeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSojuin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FlaturesSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish ThicknessSupin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesCombo D?, D*MConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSolµin (1.27µm)Ingress Protection-Auterial Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishSolyin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	Combo D?, D*M
Number of Positions8 (Coax)Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, Combo
Number of Rows1Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C) - 8W8Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	8 (Coax)
Contact TypeCoaxMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	1
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C) - 8W8
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessS0µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Coax
TerminationSolderFeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesShieldedShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Shielded
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50µin (1.27µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DCM8C8SNA222 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DCM8C8SNA222 Payment Methods



DCM8C8SNA222 Shipping Methods



If you have any question about DCM8C8SNA222, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com