

# DCMF37SEA156

### **DCMF37SEA156 Information**

Contract terres contracts terr	 DCMF37SEA156 ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 37P PNL MNT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **DCMF37SEA156** Specifications

Manufacturer ITT Cannon, LLC   Connectors, Interconnects D-Sub Connectors   Package -   Series D*M   Connector Style D*Sub Connectors   Connector Style D*Sub Connectors   Connector Style Series   Connector Style Receptacle, Female Sockets   Number of Positions 37   Shell Size, Connector Layout 4 (DC, C)   Contact Type Signal   Mounting Type Panel Mount, Through Hole   Flange Feature Solder   Features -   Shell Material, Finish Steel, Yellow Chromate Plated Zinc   Contact Finish Thickness Soljun (1.27µm)   Ingress Protection -   Material Flammability Rating UL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSipin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DCMF37SEA156
D-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Material Flammability RatingUL94 V-0	Series	D*M
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish ThicknessSoljin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeaturesHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 Yellow	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50μin (1.27μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### **DCMF37SEA156 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **DCMF37SEA156** Payment Methods



# **DCMF37SEA156 Shipping Methods**



If you have any question about DCMF37SEA156, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com