

DCMM-37S-M

equest a Quote

DCMM-37S-M Information

Heisener.com	Part Number	DCMM-37S-M
	Manufacturer	ITT Cannon, LLC
	Category	Connectors, Interconnects D-Sub Connectors
	Description	CONN D-SUB RCPT 37P PNL MNT SLDR
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DCMM-37S-M Specifications

ManufacturerITT Cannon, LLCConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-Sub ConnectorsConnector TypeReceptacle, Female SocketsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalContact TypeSolderFlange FeatureSolderFlange FeaturesSolderFeaturesSolderShell Material, FinishStel, Yellow Chromate Plated ZincContact Finish ThicknessSojin (1.27µm)Ingress ProtectionSuparvanceMaterial Flamability RatingUB4V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Mages Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DCMM-37S-M
D-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Muerial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSoljun (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSoljuin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeaturesHousing/Shell (Unthreaded)FeaturesSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)FerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50μin (1.27μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50μin (1.27μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
1		Report errors?

DCMM-37S-M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DCMM-37S-M Payment Methods



DCMM-37S-M Shipping Methods



If you have any question about DCMM-37S-M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com