

DCMME-37P-M

DCMME-37P-M Information

Heisener.com	 DCMME-37P-M ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 37P PNL MNT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DCMME-37P-M Specifications

ManufacturerITT Cannon, LLCConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-Sub ConnectorsConnector TypePlug, Male PinsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeSolder (4-40)Flange FeatureSolder (4-40)FeaturesSolder (4-40)FeaturesSolder (5-40)Shell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessSolyin (1.27µm)Ingress Protection-Material Flamaability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-Sub Connector, D*MMConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMunting TypeSolderFeaturesSolderShell Material, FinishSolderContact FinishGoldContact Finish ThicknessSoly (1.27µm)Ingress ProtectionSoly (1.27µm)	Manufacturer Part Number	DCMME-37P-M
D-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish ThicknessSupport 10.27µm)Ingress ProtectionJL94 V-0	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSolµin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessSoljuri (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeaturesBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureBoard Side (4-40)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (4-40)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50µin (1.27µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DCMME-37P-M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DCMME-37P-M Payment Methods



DCMME-37P-M Shipping Methods



If you have any question about DCMME-37P-M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com