

DCUK37S

DCUK37S Information

Contract nervice contractions	 DCUK37S ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 37POS PNL MNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DCUK37S Specifications

Anufacturer ITT Cannon, LLC Category Connectors, Interconnects Package D-Sub Connectors Package - Series D*U Connector Style D*U Connector Type Receptacle, Female Sockets Number of Positions 37 Number of Rows 2 Shell Size, Connector Layout 4(DC, C) Contact Type Signal Mounting Type Panel Mounti Flange Feature Housing/Shell (Unthreaded) Features - Shell Material, Finish Stel, Yellow Chromate Plated Zinc Contact Finish Thickness Gold Contact Finish Thickness -		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesD*UConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlarge Feature-Shell Material, FinishStel, Yellow Chromate Plated ZincShell Material, FinishGoldContact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DCUK37S
D-Sub ConnectorsPackage-SeriesD*UConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpShell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesD*UConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpShell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesD*UConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish-Ingress Protection-Material Flammability RatingUL94 V-0	Series	D*U
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	37
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationCrimpFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Crimp
Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	-
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DCUK37S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DCUK37S Payment Methods





If you have any question about DCUK37S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com