

DD50P365TXLF

DD50P365TXLF Information

Heisener.com	Part Number Manufacturer Category Description Package	DD50P365TXLF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 50POS VERT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DD50P365TXLF Specifications

SeriesDConnector StyleD-SubConnector TypePlug, Male PinsNumber of PositionsS0Number of Rows3Shell Size, Connector LayoutS (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishSicel, Tin PlatedContact FinishSolderShell Material, FinishSteel, Tin PlatedContact FinishSicel, Tin PlatedContact FinishSicel, Tin PlatedContact Finish ThicknessSignal		
CategoryConnectors, Interconnects D-Sub ConnectorsPackage-SeriesDConnector StyleD-SubConnector TypePlug, Male PinsNumber of PositionsS0Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DD50P365TXLF
PackageD-Sub ConnectorsPackage-SeriesDConnector StyleD-SubConnector TypePlug, Male PinsNumber of PositionsS0Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold, GXT?Contact Finish ThicknessJujin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDConnector StyleD-SubConnector TypePlug, Male PinsNumber of PositionsS0Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessJuin (0.76µm)Ingress Protection-Metrial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishSignalContact FinishSiderShell Material, FinishSiderShell Material, FinishSider, Sider, Si		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessSignin (0.76µm)Ingress ProtectionJun (0.76µm)Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeaturesSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessJuin (0.76µm)Ingress ProtectionJuin (0.76µm)Material Flanmability RatingUL94 V-0	Series	D
Number of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold, GXT?Ingress ProtectionJuin (0.76µm)Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessJujin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	50
Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessJuin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	3
Mounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish ThicknessJopin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	5 (DD, D)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole
FeaturesGrounding IndentsShell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Tin PlatedContact FinishGold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGold, GXT?Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Grounding Indents
Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold, GXT?
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DD50P365TXLF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DD50P365TXLF Payment Methods



DD50P365TXLF Shipping Methods



If you have any question about DD50P365TXLF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com