

# **DDMM50SA101**

uest a Quote

#### **DDMM50SA101 Information**

Heisener.com	Part Number	DDMM50SA101
	Manufacturer	ITT Cannon, LLC
	Category	Connectors, Interconnects D-Sub Connectors
	Description	CONN D-SUB RCPT 50POS PNL MNT
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **DDMM50SA101 Specifications**

Manufacturer Part Number DDMM50SA101   Manufacturer ITT Cannon, LLC   Category Connectors, Interconnects   D-Sub Connectors D-Sub Connectors   Package -   Series MIL-DTL-24308, D*MM   Connector Style D-Sub   Connector Type Receptacle, Female Sockets   Number of Positions 50   Number of Rows 3   Shell Size, Connector Layout 5 (DD, D)   Contact Type Signal   Mounting Type Panel Mount   Flange Feature Solder Cup   Features -   Shell Material, Finish Steel, Yellow Chromate Plated Cadmium   Contact Finish Thickness Gold   Contact Finish Thickness 50/up (1.27µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFlange Features-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Shell Material, FinishSolin (1.27µm)Ingress Protection9.129µNIngress Protection1.294 V-0	Manufacturer Part Number	DDMM50SA101
PackageD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeMandenuMunting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Flange Features-Shell Material, FinishSolder CupContact FinishGoldContact FinishSoly (Li Zjum)Ingress Protection-Metrial Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishStell Yell Mutheraded)Contact FinishGoldContact Finish ThicknessSolin (127µm)Ingress Protection-Material Flammability RatingU54 Vel	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSoljuri (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSoljun (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	50
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	3
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	5 (DD, D)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder Cup
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Cadmium
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50µin (1.27µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
1		Report errors?

#### **DDMM50SA101** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **DDMM50SA101** Payment Methods



## **DDMM50SA101** Shipping Methods



If you have any question about DDMM50SA101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com