

DDMR50S

DDMR50S Information

Heisener.com Endelserver statistier	 DDMR50S ITT Cannon, LLC Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 50POS PNL MNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DDMR50S Specifications

Manufacturer ITT Cannon, LLC Category Connectors, Interconnects D-Sub Connectors D-Sub Connectors Package - Series D*M Connector Style D*M Connector Type Receptacle, Female Sockets Number of Positions So Number of Rows 3 Shell Size, Connector Layout Signal Mounting Type Panel Mount Flange Feature Solder Cup Flange Feature Solder Cup Flanger Finish Stell S		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Shell Size, Connector LayoutSignalContact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress ProtectionFlashMaterial Flammability RatingUL94 V-0	Manufacturer Part Number	DDMR50S
D-Sub ConnectorsPackage-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypePanel MountMunting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupShell Material, FinishStel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesD*MConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupTerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0	Series	D*M
Number of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	50
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	3
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	5 (DD, D)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated ZincContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder Cup
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Zinc
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DDMR50S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DDMR50S Payment Methods



DDMR50S Shipping Methods



If you have any question about DDMR50S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com