



DE3S062D0L Information



For Reference Only

Part Number DE3S062D0L

Manufacturer Panasonic Electronic Components

Category Circuit Protection TVS - Diodes

Description TVS DIODE 4VWM SSMINI3F3B

Package SC-89, SOT-490

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DE3S062D0L Specifications

Manufacturer Part NumberDE3S062D0LManufacturerPanasonic Electronic ComponentsCategoryCircuit ProtectionTVS - DiodesPackageSC-89, SOT-490Series-TypeZenerUnidirectional Channels2Bidirectional Channels-Voltage - Reverse Standoff (Typ)4VVoltage - Breakdown (Min)5.89VVoltage - Clamping (Max) @ Ipp-
Category Circuit Protection TVS - Diodes Package SC-89, SOT-490 Series - Type Zener Unidirectional Channels 2 Bidirectional Channels - Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) Circuit Protection TVS - Diodes SC-89, SOT-490 - 4 Vener Zener 4 Voltage - Breakdown (Min) 5.89V
TVS - Diodes Package SC-89, SOT-490 Series - Type Zener Unidirectional Channels 2 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 4V Voltage - Breakdown (Min) 5.89V
Package SC-89, SOT-490 Series - Type Zener Unidirectional Channels 2 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 4V Voltage - Breakdown (Min) 5.89V
Series - Type Zener Unidirectional Channels 2 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 4V Voltage - Breakdown (Min) 5.89V
Type Zener Unidirectional Channels 2 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 4V Voltage - Breakdown (Min) 5.89V
Unidirectional Channels Bidirectional Channels Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 5.89V
Bidirectional Channels Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 5.89V
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 4V 5.89V
Voltage - Breakdown (Min) 5.89V
-
Voltage - Clamping (Max) @ Ipp
Current - Peak Pulse (10/1000µs)
Power - Peak Pulse -
Power Line Protection No
Applications General Purpose
Capacitance @ Frequency 55pF @ 1MHz
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type Surface Mount
Package / Case SC-89, SOT-490
Supplier Device Package SSMini3-F3-B
Report errors?

DE3S062D0L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DE3S062D0L Payment Methods



















DE3S062D0L Shipping Methods













If you have any question about DE3S062D0L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com