



DE6E3KJ222MA3B Information



For Reference Only

Part Number DE6E3KJ222MA3B

Manufacturer Murata
Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 300VAC RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DE6E3KJ222MA3B Specifications

Manufacturer Part Number DE6E3KJ222MA3B Manufacturer Murata Category Capacitors Package Radial, Disc Series KJ Capacitance 2200pF Tolerance ±20% Voltage - Rated 300VAC Temperature Coefficient E Operating Temperature 40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads		
Category Capacitors Package Radial, Disc Series KJ Capacitance 2200pF Tolerance ±20% Voltage - Rated 300VAC Temperature Coefficient E Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Manufacturer Part Number	DE6E3KJ222MA3B
Package Radial, Disc Series KJ Capacitance 2200pF Tolerance ±20% Voltage - Rated 300VAC Temperature Coefficient E Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Manufacturer	Murata
PackageRadial, DiscSeriesKJCapacitance2200pFTolerance±20%Voltage - Rated300VACTemperature CoefficientEOperating Temperature-40°C ~ 125°CFeaturesHigh VoltageRatingsAEC-Q200, X1, Y2ApplicationsSafety, AutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.472" (12.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleFormed Leads	Category	Capacitors
SeriesKJCapacitance2200pFTolerance±20%Voltage - Rated300VACTemperature CoefficientEOperating Temperature-40°C ~ 125°CFeaturesHigh VoltageRatingsAEC-Q200, X1, Y2ApplicationsSafety, AutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.472" (12.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleFormed Leads		Ceramic Capacitors
Capacitance 2200pF Tolerance ±20% Voltage - Rated 300VAC Temperature Coefficient E Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Package	Radial, Disc
Tolerance ±20% Voltage - Rated 300VAC Temperature Coefficient E Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style	Series	KJ
Voltage - Rated300VACTemperature CoefficientEOperating Temperature-40°C ~ 125°CFeaturesHigh VoltageRatingsAEC-Q200, X1, Y2ApplicationsSafety, AutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.472" (12.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleFormed Leads	Capacitance	2200pF
Temperature Coefficient Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style	Tolerance	±20%
Operating Temperature -40°C ~ 125°C Features High Voltage Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Voltage - Rated	300VAC
Features Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Temperature Coefficient	Е
Ratings AEC-Q200, X1, Y2 Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Operating Temperature	-40°C ~ 125°C
Applications Safety, Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Features	High Voltage
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Ratings	AEC-Q200, X1, Y2
Mounting Type Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Applications	Safety, Automotive
Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Radial, Disc 0.354" Dia (9.00mm)	Failure Rate	-
Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.472" (12.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.472" (12.00mm) - 0.295" (7.50mm) Formed Leads	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.295" (7.50mm) Lead Style Formed Leads	Size / Dimension	0.354" Dia (9.00mm)
Lead Spacing0.295" (7.50mm)Lead StyleFormed Leads	Height - Seated (Max)	0.472" (12.00mm)
Lead Style Formed Leads	Thickness (Max)	-
·	Lead Spacing	0.295" (7.50mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

DE6E3KJ222MA3B Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DE6E3KJ222MA3B Payment Methods



















DE6E3KJ222MA3B Shipping Methods













If you have any question about DE6E3KJ222MA3B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com