

DEV2V2P500G30LF

DEV2V2P500G30LF Information

| Heisener.com | DEV2V2P500G30LF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 2POS R/A SOLDER - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DEV2V2P500G30LF Specifications

| Manufacturer Amphenol FCI Category Connectors, Interconnects D-Sub Connectors D-Sub Connectors Package - Series DW Connector Style D-Sub, Combo Connector Type Plug, Female Sockets and Male Pins Number of Positions 2 (Power) Number of Rows 1 Shell Size, Connector Layout 1 (DE, E) - 2V2, 2W2C Contact Type Power Mounting Type Through Hole, Right Angle Flange Feature Solder Flange Feature Solder Features Board Lock, Grounding Indents, Mounting Brackets Shell Material, Finish Steel, Tin Plated Contact Finish Thickness - Contact Finish Thickness - Shell Material Flammability Rating UL94 V-0 | | |
|---|------------------------------|--|
| CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Manufacturer Part Number | DEV2V2P500G30LF |
| D-Sub ConnectorsPackage-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderShell Material, FinishSolderContact FinishGoldContact Finish Thickness-Auterial Flammability RatingUL94 V-0 | Manufacturer | Amphenol FCI |
| Package-SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress ProtectionJUE V-0Material Flammability RatingUL94 V-0 | Category | Connectors, Interconnects |
| SeriesDWConnector StyleD-Sub, ComboConnector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | | D-Sub Connectors |
| Connector StyleD-Sub, ComboConnector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Angress ProtectionUL94 V-0 | Package | - |
| Connector TypePlug, Female Sockets and Male PinsNumber of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress ProtectionUL94 V-0 | Series | DW |
| Number of Positions2 (Power)Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Connector Style | D-Sub, Combo |
| Number of Rows1Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishStel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Connector Type | Plug, Female Sockets and Male Pins |
| Shell Size, Connector Layout1 (DE, E) - 2V2, 2W2CContact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Number of Positions | 2 (Power) |
| Contact TypePowerMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Number of Rows | 1 |
| Nounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Shell Size, Connector Layout | 1 (DE, E) - 2V2, 2W2C |
| Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Contact Type | Power |
| TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Mounting Type | Through Hole, Right Angle |
| FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Flange Feature | Mating Side, Female Screwlock (4-40) |
| Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Termination | Solder |
| Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Features | Board Lock, Grounding Indents, Mounting Brackets |
| Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0 | Shell Material, Finish | Steel, Tin Plated |
| Ingress Protection-Material Flammability RatingUL94 V-0 | Contact Finish | Gold |
| Material Flammability Rating UL94 V-0 | Contact Finish Thickness | - |
| | Ingress Protection | - |
| | Material Flammability Rating | UL94 V-0 |
| Report errors? | | Report errors? |

DEV2V2P500G30LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DEV2V2P500G30LF Payment Methods





If you have any question about DEV2V2P500G30LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com