

DF10-31S-2DSA(62)

DF10-31S-2DSA(62) Information

www.httscher.com		DF10-31S-2DSA(62) Hirose Electric Co Ltd Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
and the second sec	Description	CONNECTOR 31 PIN FEMALE STRAIGHT	27206223
	Package	-	回記に報い
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DF10-31S-2DSA(62) Specifications

ManufacturerHirose Electric Co LdCategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDF10Connector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions Loaded1Number of Rows1Number of Rows1Number of Rows1Number of Rows1Style-Style-Style-Style0.079" (2.00mm)Number of Rows1Number of Rows1Style-Style				
CategoryConnectorsCategoryConnectors, InterconnectsPackage-Package-SeriesDF10Connector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedINumber of Rows1Number of Rows1Number of RowsSinked Pin SolderNumber of Rows1Style-String TypeSinked Pin SolderNumber of Rows1String TypeSinked Pin SolderString TypeSinked Pin SolderString TypeSinked Pin SolderString TypeSoldContact Finish - MatingSoldContact Finish - MatingSinkin Cloupm)String TypeSolderString Type<	Manufacturer Part Number	DF10-31S-2DSA(62)		
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDF10Connector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - Mating3.9µin (0.10µm)Insulation ColorBlack	Manufacturer	Hirose Electric Co Ltd		
Package-SeriesDF10Conector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedAllNumber of Rows0.079° (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeInrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldContact Finish - MatingSign (0.10µm)Insulation ColorBlack	Category	Connectors, Interconnects		
SeriesDF10Connector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedAllNumber of Rows0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldContact Finish Thickness - MatingBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedAllNumber of Rows0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFerminationKinked Pin, SolderFortact Finish - MatingGoldContact Finish - Mating3.9µin (0.10µm)Insulation ColorBlack	Package	-		
Contact TypeFemale SocketStyle-Number of Positions31Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOolContact Finish - MatingGoldContact Finish - MatingSipin (0.10µm)Insulation ColorBlack	Series	DF10		
Style-Style-Number of Positions31Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldIonater Finish - Mating3.9µin (0.10µm)Insulation ColorBlack	Connector Type	Receptacle		
Number of Positions31Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Style	-		
Pitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldSolnater Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Number of Positions	31		
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Number of Positions Loaded	All		
Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Pitch - Mating	0.079" (2.00mm)		
Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Number of Rows	1		
TerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Row Spacing - Mating	-		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Mounting Type	Through Hole		
Contact Finish - MatingGoldContact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Termination	Kinked Pin, Solder		
Contact Finish Thickness - Mating3.9µin (0.10µm)Insulation ColorBlack	Fastening Type	Push-Pull		
Insulation Color Black	Contact Finish - Mating	Gold		
	Contact Finish Thickness - Mating	3.9µin (0.10µm)		
	Insulation Color	Black		
Insulation Height 0.157" (4.00mm)	Insulation Height	0.157" (4.00mm)		
Contact Length - Post 0.110" (2.79mm)	Contact Length - Post	0.110" (2.79mm)		
Operating Temperature $-30^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Temperature	-30°C ~ 85°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

DF10-31S-2DSA(62) Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DF10-31S-2DSA(62) Payment Methods



If you have any question about DF10-31S-2DSA(62), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com