

DF13-40DS-1.25DSA(55)

DF13-40DS-1.25DSA(55) Information

		DF13-40DS-1.25DSA(55) Hirose Electric Co Ltd	
www.heisener.com	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RECEPT 40POS 1.25MM GOLD	10000000
	Package	-	日本の長い
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DF13-40DS-1.25DSA(55) Specifications

Manufacturer Part NumberDF13-40DS-1.25DSA(55)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDF13Connector TypeReceptacles, Genetacles, Female SocketsContact TypeReceptacleContact TypeBoard to Board or CableNumber of PositionsAulNumber of Positions LoadedAllNumber of Rows2Row Spacing - MatingOld9" (1.25mm)Mounting TypeIntrough HoleTerninationSolderContact Finish - MatingGoldContact Finish - MatingGoldStriet Finish - MatingGoldStriet Finish - MatingGoldStriet Finish - MatingGoldContact Finish Thickness - MatingBigeInsulation ColorBigeInsulation ColorGold?Contact Finish Thickness - MatingJ.97" (Somm)Contact Linish ThicknessJ.97" (Somm)Contact Linish ThicknessJ.97" (Somm)Contact Linish Thickness </th <th></th> <th></th>		
CategoryConnectors - Headers, Receptacles, Female SocketsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDF13Connector TypeReceptacleContact TypeReceptacleStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.049" (1.25mm)Number of Rows0.049" (1.25mm)Number of Rows0.049" (1.25mm)Row Spacing - MatingOideStore TypeFriction LockContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBeigeInsulation Flexes - MatingIngonyInsulation Flexes - Mating0.197" (S.Omm)Contact Length - Post0.709" (2.00mn)Operating Temperature0.35°C + 85°C	Manufacturer Part Number	DF13-40DS-1.25DSA(55)
Package-SeriesDF13Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBoard to CableStyleSolderFastening TypeFriction LockContact Finish Thickness - MatingBeigeInsulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35"C ~ 85"C	Manufacturer	Hirose Electric Co Ltd
Package-SeriesDF13Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBigeInsulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature35°C ~ 85°C	Category	Connectors, Interconnects
SeriesDF13Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllNumber of Rows2Number of Rows0.049" (1.25mm)Number of Rows0.049" (1.25mm)Number of Rows0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldSoltar Finish Thickness - MatingBigeInsulation ColorBigeInsulation Height0.197" (5.00mm)Contact Length - Post0.79" (2.00mn)Operating Temperature-35°C ~ 85°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeO1049" (1.25mm)TerminationSolderTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.707" (2.00mm)Operating Temperature-35°C ~ 85°C	Package	-
Contact TypeFendle SocketStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBeigeInsulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Series	DF13
StyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeD409" (1.25mm)TerminationSolderFastening TypeFriction LockContact Finish - MatingGoldInsulation ColorBigieInsulation Height0.197" (5.00mm)Contact Length - Post35°C ~ 85°C	Connector Type	Receptacle
Number of Positions 40 Number of Positions Loaded All Pitch - Mating 0.049" (1.25mm) Number of Rows 2 Row Spacing - Mating 0.049" (1.25mm) Mounting Type 0.049" (1.25mm) Termination Solder Fastening Type Friction Lock Contact Finish - Mating Gold Contact Finish Thickness - Mating Beige Insulation Color Beige Insulation Height 0.197" (5.00mm) Contact Length - Post 0.079" (2.00mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBeigeInsulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Style	Board to Board or Cable
Pitch - Mating0.049" (1.25mm)Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting Type0.049" (1.25mm)TerminationThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBeigeInsulation Color0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature35°C ~ 85°C	Number of Positions	40
Number of Rows2Row Spacing - Mating0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBujin (0.20µm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Number of Positions Loaded	All
Row Spacing - Mating0.049" (1.25mm)Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBujn (0.20µm)Insulation Color0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Pitch - Mating	0.049" (1.25mm)
Mounting TypeThrough HoleTerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - MatingBuin (0.20µm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Number of Rows	2
TerminationSolderFastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - Mating&µin (0.20µm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Row Spacing - Mating	0.049" (1.25mm)
Fastening TypeFriction LockContact Finish - MatingGoldContact Finish Thickness - Mating&µin (0.20µm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating&µin (0.20µm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Termination	Solder
Contact Finish Thickness - Mating8μin (0.20μm)Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Fastening Type	Friction Lock
Insulation ColorBeigeInsulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Contact Finish - Mating	Gold
Insulation Height0.197" (5.00mm)Contact Length - Post0.079" (2.00mm)Operating Temperature-35°C ~ 85°C	Contact Finish Thickness - Mating	8μin (0.20μm)
Contact Length - Post 0.079" (2.00mm) Operating Temperature -35°C ~ 85°C	Insulation Color	Beige
Operating Temperature $-35^{\circ}C \sim 85^{\circ}C$	Insulation Height	0.197" (5.00mm)
	Contact Length - Post	0.079" (2.00mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-35°C ~ 85°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	6.8mm
Ingress Protection	-
Features	Pick and Place

Report errors?

DISCOVER

DF13-40DS-1.25DSA(55) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DF13-40DS-1.25DSA(55) Payment Methods

DF13-40DS-1.25DSA(55) Shipping Methods



If you have any question about DF13-40DS-1.25DSA(55), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com