

**DF14A-8P-1.25H(56) Information**


For Reference Only

**Part Number** [DF14A-8P-1.25H\(56\)](#)  
**Manufacturer** Hirose Electric Co Ltd  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER 8POS 1.25MM R/A SMD  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



Request a Quote

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**DF14A-8P-1.25H(56) Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">DF14A-8P-1.25H(56)</a>   |
| Manufacturer               | Hirose Electric Co Ltd   |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | DF14   |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.049" (1.25mm)  |
| Style                      | Board to Cable/Wire  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 8  |
| Number of Positions Loaded | All  |
| Number of Rows             | 1  |
| Row Spacing - Mating       | -  |
| Mounting Type              | Surface Mount, Right Angle   |
| Termination                | Solder   |
| Fastening Type             | Push-Pull  |
| Contact Length - Mating    | 0.086" (2.20mm)  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.098" (2.50mm)  |
| Contact Shape              | Square   |
| Contact Finish - Mating    | Gold   |

|                                   |                                |
|-----------------------------------|--------------------------------|
| Contact Finish Thickness - Mating | 3.9μin (0.10μm)                |
| Contact Finish - Post             | Tin-Copper                     |
| Contact Material                  | Brass                          |
| Insulation Material               | Polyamide (PA), Nylon          |
| Features                          | Solder Retention               |
| Operating Temperature             | -35°C ~ 85°C                   |
| Ingress Protection                | -                              |
| Material Flammability Rating      | UL94 V-0                       |
| Insulation Color                  | Beige                          |
|                                   | <a href="#">Report errors?</a> |

## DF14A-8P-1.25H(56) Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DF14A-8P-1.25H(56) Payment Methods



## DF14A-8P-1.25H(56) Shipping Methods



If you have any question about DF14A-8P-1.25H(56), please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)