

DF3A-2P-2DSA(17)

DF3A-2P-2DSA(17) Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DF3A-2P-2DSA(17) Specifications

Manufacturer Part Number	DF3A-2P-2DSA(17)
Manufacturer	Hirose Electric Co Ltd
Category	Connectors, Interconnects
	Rectangular Connectors - Headers, Male Pins
Package	-
Series	DF3
Connector Type	Header
Contact Type	Male Pin
Pitch - Mating	0.079" (2.00mm)
Style	Board to Board or Cable
Shrouding	Shrouded - 4 Wall
Number of Positions	2
Number of Positions Loaded	All
Number of Rows	1
Row Spacing - Mating	-
Mounting Type	Through Hole
Termination	Press-Fit, Solder
Fastening Type	Push-Pull
Contact Length - Mating	0.122" (3.10mm)
Contact Length - Post	0.114" (2.90mm)
Overall Contact Length	0.299" (7.60mm)
Insulation Height	0.197" (5.00mm)
Contact Shape	Square
Contact Finish - Mating	Tin

E-mail: salesdept@heisener.com

Contact Finish Thickness - Mating	-
Contact Finish - Post	Tin
Contact Material	Brass
Insulation Material	Polyamide (PA), Nylon
Features	-
Operating Temperature	-55°C ~ 105°C
Ingress Protection	-
Material Flammability Rating	UL94 V-0
Insulation Color	-
	Report errors?

DF3A-2P-2DSA(17) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DF3A-2P-2DSA(17) Payment Methods



If you have any question about DF3A-2P-2DSA(17), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com