

**DF3Z-11P-2V(21) Information**


For Reference Only

**Part Number** [DF3Z-11P-2V\(21\)](#)  
**Manufacturer** Hirose Electric Co Ltd  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HDR 11POS 2MM VERT GOLD  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



Request a Quote

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**DF3Z-11P-2V(21) Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">DF3Z-11P-2V(21)</a>  |
| Manufacturer               | Hirose Electric Co Ltd   |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | DF3  |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.079" (2.00mm)  |
| Style                      | Board to Board or Cable  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 11   |
| Number of Positions Loaded | All  |
| Number of Rows             | 1  |
| Row Spacing - Mating       | -  |
| Mounting Type              | Surface Mount  |
| Termination                | Solder   |
| Fastening Type             | Push-Pull  |
| Contact Length - Mating    | -  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.232" (5.90mm)  |
| Contact Shape              | Circular   |
| Contact Finish - Mating    | Tin  |

|                                   |                               |
|-----------------------------------|-------------------------------|
| Contact Finish Thickness - Mating | -                             |
| Contact Finish - Post             | Tin                           |
| Contact Material                  | Brass                         |
| Insulation Material               | Polyamide (PA), Nylon         |
| Features                          | Board Guide, Solder Retention |
| Operating Temperature             | -55°C ~ 105°C                 |
| Ingress Protection                | -                             |
| Material Flammability Rating      | UL94 V-0                      |
| Insulation Color                  | Beige                         |
| <a href="#">Report errors?</a>    |                               |

## DF3Z-11P-2V(21) Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DF3Z-11P-2V(21) Payment Methods



## DF3Z-11P-2V(21) Shipping Methods



If you have any question about DF3Z-11P-2V(21), please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)