

DF59-2P-2FC(50) Information



For Reference Only

Part Number DF59-2P-2FC(50)

Manufacturer Hirose Electric Co Ltd

Category Connectors, Interconnects
Solid State Lighting Connectors

Description CONN SSL BRIDGE 2POS 2MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DF59-2P-2FC(50) Specifications

Manufacturer Part NumberDF59-2P-2FC(50)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-SeriesDF59StyleBoard to BoardConnector TypeAdapter, BridgeNumber of Positions2Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C		
Category Connectors, Interconnects Solid State Lighting Connectors Package - Series DF59 Style Board to Board Connector Type Adapter, Bridge Number of Positions 2 Mounting Type Push Mount, Snap-In Termination - Pitch 0.079" (2.00mm) Fastening Type - Features - Housing Color Natural Wire Gauge Contact Material Contact Finish Gold Housing Material Operating Temperature Contact Sale Lighting Connectors - Solid State Lighting Connectors - Sol	Manufacturer Part Number	DF59-2P-2FC(50)
Package-SeriesDF59StyleBoard to BoardConnector TypeAdapter, BridgeNumber of Positions2Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Manufacturer	Hirose Electric Co Ltd
Package-SeriesDF59StyleBoard to BoardConnector TypeAdapter, BridgeNumber of Positions2Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Category	Connectors, Interconnects
Series DF59 Style Board to Board Connector Type Adapter, Bridge Number of Positions 2 Mounting Type Push Mount, Snap-In Termination - Pitch 0.079" (2.00mm) Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -		Solid State Lighting Connectors
StyleBoard to BoardConnector TypeAdapter, BridgeNumber of Positions2Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Package	-
Connector Type Adapter, Bridge Number of Positions 2 Mounting Type Push Mount, Snap-In Termination - Pitch 0.079" (2.00mm) Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Series	DF59
Number of Positions2Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Style	Board to Board
Mounting TypePush Mount, Snap-InTermination-Pitch0.079" (2.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Connector Type	Adapter, Bridge
Termination - Pitch 0.079" (2.00mm) Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Number of Positions	2
Pitch 0.079" (2.00mm) Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Mounting Type	Push Mount, Snap-In
Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Termination	-
Features - Housing Color Natural Wire Gauge - Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Pitch	0.079" (2.00mm)
Housing Color Wire Gauge Contact Material Brass Contact Finish Gold Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Fastening Type	-
Wire Gauge Contact Material Brass Contact Finish Gold Housing Material Operating Temperature Polybutylene Terephthalate (PBT) -35°C ~ 105°C	Features	-
Contact MaterialBrassContact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature $-35^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Housing Color	Natural
Contact FinishGoldHousing MaterialPolybutylene Terephthalate (PBT)Operating Temperature -35° C $\sim 105^{\circ}$ C	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT) Operating Temperature $-35^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	Brass
Operating Temperature $-35^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	Gold
	Housing Material	Polybutylene Terephthalate (PBT)
Report errors?	Operating Temperature	-35°C ~ 105°C
		Report errors?

DF59-2P-2FC(50) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DF59-2P-2FC(50) Payment Methods





















DF59-2P-2FC(50) Shipping Methods













If you have any question about DF59-2P-2FC(50), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com