

DF59-3P-2C Information

Part Number DF59-3P-2C

Manufacturer Hirose Electric Co Ltd Category Connectors, Interconnects **Solid State Lighting Connectors**

Description CONN SSL RCPT HSG 3POS 2MM CRIMP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DF59-3P-2C Specifications

Manufacturer Part Number DF59-3P-2C Manufacturer Hirose Electric Co Ltd Category Connectors, Interconnects Solid State Lighting Connectors Package - Series DF59 Style Board to Cable/Wire Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C Report errors?		
Category Connectors, Interconnects Solid State Lighting Connectors Package - Series DF59 Style Board to Cable/Wire Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge Contact Material Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature	Manufacturer Part Number	DF59-3P-2C
Solid State Lighting Connectors Package - Series DF59 Style Board to Cable/Wire Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material Contact Finish - Housing Material Operating Temperature -35°C ~ 105°C	Manufacturer	Hirose Electric Co Ltd
Package - DF59 Style Board to Cable/Wire Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Material Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature - Sor C ~ 105°C	Category	Connectors, Interconnects
Series DF59 Style Board to Cable/Wire Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C		Solid State Lighting Connectors
StyleBoard to Cable/WireConnector TypeReceptacle Housing for Socket ContactNumber of Positions3Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.079" (2.00mm)Fastening TypeSwing LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Package	-
Connector Type Receptacle Housing for Socket Contact Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Series	DF59
Number of Positions3Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.079" (2.00mm)Fastening TypeSwing LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Style	Board to Cable/Wire
Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.079" (2.00mm)Fastening TypeSwing LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-35°C ~ 105°C	Connector Type	Receptacle Housing for Socket Contact
Termination Crimp Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Number of Positions	3
Pitch 0.079" (2.00mm) Fastening Type Swing Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Mounting Type	Free Hanging (In-Line)
Fastening Type Features - Housing Color Natural Wire Gauge - Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT) Operating Temperature Swing Lock - Polybutylene Polybutylene Polybutylene Polybutylene Polybutylene Polybutylene Polybutylene Polybutylene	Termination	Crimp
Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Pitch	0.079" (2.00mm)
Housing Color Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Fastening Type	Swing Lock
Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Features	-
Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Housing Color	Natural
Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -35°C ~ 105°C	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT) Operating Temperature $-35^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-35^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polybutylene Terephthalate (PBT)
Report errors?	Operating Temperature	-35°C ~ 105°C
		Report errors?

DF59-3P-2C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DF59-3P-2C Payment Methods



















DF59-3P-2C Shipping Methods













If you have any question about DF59-3P-2C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com