

DFJ-90 Information

wo helsener.com

For Reference Only

Part Number DFJ-90 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 90A 600VAC/450VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DFJ-90 Specifications

Manufacturer Part Number DFJ-90 Manufacturer Eaton Category Circuit Protection Beckage Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series DFJ Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 600V Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)		
Category Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series DFJ Fuse Type Cartridge Current Rating 90A Voltage Rating - AC Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Current Rating PoA Cartridge C	Manufacturer Part Number	DFJ-90
Flectrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series DFJ Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 600V Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features CE, CSA, UL CE, CSA, UL COperating Temperature Solt Mount Size / Dimension I 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesDFJFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Category	Circuit Protection
Series DFJ Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 600V Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 90A 600V	Series	DFJ
Voltage Rating - AC Voltage Rating - DC 450V Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 450V 600V 600V 450V 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 450V 450V 450V 450V 450V 450V 450V 650V 6600 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000 6000	Current Rating	90A
Response Time - Applications - Electrical, Industrial - Class - Class - J - Approvals - CE, CSA, UL - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type - Bolt Mount - Package / Case - Cylindrical, Blade Terminal (Bolt) - Size / Dimension - 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Voltage Rating - DC	450V
Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Response Time	-
Class Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension J CE, CSA, UL CB, CSA, UL CE, CSA, UL CE, CSA, UL CUL CUL CUL CUL CUL CUL CUL	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Class	J
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.130" Dia x 2.630" L (28.70mm x 66.80mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.130" Dia x 2.630" L (28.70mm x 66.80mm)
		Report errors?

DFJ-90 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DFJ-90 Payment Methods





















DFJ-90 Shipping Methods













If you have any question about DFJ-90, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com