

# DG120M-9

a Quote

### **DG120M-9 Information**

Part Number	DG120M-9	
Manufacturer	Curtis Industries	
Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	- 540
Description	AC/DC CONVERTER 24V 120W	- 32G
Package	-	- Heister
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request
	Manufacturer Category Description	Manufacturer Curtis Industries   Category Power Supplies - External/Internal (Off-Board) AC DC Converters   Description AC/DC CONVERTER 24V 120W   Package -   For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### **DG120M-9** Specifications

Manufacturer Part NumberDG120M-9ManufacturerCurtis IndustriesCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesTri-Mag, DG120TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Power (Watts)120W (150W Forced Air)Power (Watts)120W (150W Forced Air)Applications4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChasis Mount		
CategoryFourmationCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesTri-Mag, DG120TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 45APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4KV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesFEC, Universal Input	Manufacturer Part Number	DG120M-9
AC DC ConvertersPackage-SeriesTri-Mag, DG120TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 45APower (Watts)120W (150W Forced Air)ApplicationsKedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Manufacturer	Curtis Industries
Package.SeriesTri-Mag, DG120TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 124VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 4.Power (Wats)I20W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4XV (4000V)Efficiency90%Operating TemperatureFC, Universal Input	Category	Power Supplies - External/Internal (Off-Board)
SeriesTri-Mag, DG120TypeOpen FrameNumber of Outputs1Voltage - Output90 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 45APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesFC, Universal Input		AC DC Converters
Type   Open Frame     Number of Outputs   1     Voltage of Outputs   90 ~ 264 VAC     Voltage - Output 1   24V     Voltage - Output 2   -     Voltage - Output 3   -     Voltage - Output 4   -     Voltage - Output 5   -     Voltage - Output 4   -     Voltage - Output 4   -     Voltage - Soluput 4   -     Voltage - Soluput 4   -     Voltage - Soluput 5   -     Voltage - Soluput 6   -     Voltage - Isolation   -     Voltage - Isolation   -     Voltage - Soluput 7   -     Voltage	Package	-
Number of Outputs   I     Number of Outputs   1     Voltage - Input   90 ~ 264 VAC     Voltage - Output 1   24V     Voltage - Output 2   -     Voltage - Output 3   -     Voltage - Output 4   -     Current - Output (Max)   5A     Power (Watts)   120W (150W Forced Air)     Applications   Medical     Voltage - Isolation   4kV (4000V)     Efficiency   90%     Operating Temperature   -20°C ~ 70°C (With Derating)     Features   PFC, Universal Input	Series	Tri-Mag, DG120
Voltage - Input   90 ~ 264 VAC     Voltage - Output 1   24V     Voltage - Output 2   -     Voltage - Output 3   -     Voltage - Output 4   -     Current - Output (Max)   5A     Power (Watts)   120W (150W Forced Air)     Applications   Medical     Voltage - Isolation   4kV (4000V)     Efficiency   90%     Operating Temperature   -20°C ~ 70°C (With Derating)     Features   PFC, Universal Input	Туре	Open Frame
Voltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Number of Outputs	1
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Output 1	24V
Voltage - Output 4-Current - Output (Max)5APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Output 2	-
Current - Output (Max)5APower (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Output 3	-
Power (Watts)120W (150W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Output 4	-
ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Current - Output (Max)	5A
InActionVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Power (Watts)	120W (150W Forced Air)
Efficiency90%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Applications	Medical
Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal Input	Voltage - Isolation	4kV (4000V)
Features PFC, Universal Input	Efficiency	90%
	Operating Temperature	$-20^{\circ}$ C ~ $70^{\circ}$ C (With Derating)
Mounting Type Chassis Mount	Features	PFC, Universal Input
	Mounting Type	Chassis Mount
Size / Dimension 4.00" L x 2.00" W x 1.28" H (101.6mm x 50.8mm x 32.5mm)	Size / Dimension	4.00" L x 2.00" W x 1.28" H (101.6mm x 50.8mm x 32.5mm)
Report error		Report errors?

#### **DG120M-9** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## DG120M-9 Payment Methods





If you have any question about DG120M-9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com