

DG200-14EC Information

Heisener.com

Part Number DG200-14EC
Manufacturer Curtis Industries

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 200W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DG200-14EC Specifications

Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer Part Number	DG200-14EC	
AC DC Converters	Manufacturer	Curtis Industries	
Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Series	Tri-Mag, DG200	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Туре	Enclosed	
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Number of Outputs	1	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 200W (300W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Apower (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Pectures PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension Size / Dimension - Output (Max) 4.2A - Current - Output (Max) 4.2A Power (Watts) Author (Watts) - Commercial) 4kV (4000V) For (With Derating) PFC, Standby Output, Universal Input Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 1	48V	
Voltage - Output 4 Current - Output (Max) 4.2A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension -20°L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.2A 4.2A 200W (300W Forced Air) ITE (Commercial) 4kV (4000V) 90% Chassis Mount Features PFC, Standby Output, Universal Input Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 200W (300W Forced Air) 1TE (Commercial) 4kV (4000V) 90% Chassis Moutput, Universal Input Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Current - Output (Max)	4.2A	
Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Power (Watts)	200W (300W Forced Air)	
Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Applications	ITE (Commercial)	
Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Isolation	4kV (4000V)	
Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Efficiency	90%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Operating Temperature	-20°C ~ 65°C (With Derating)	
Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Features	PFC, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	
			Report errors?

DG200-14EC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DG200-14EC Payment Methods



















DG200-14EC Shipping Methods













If you have any question about DG200-14EC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com