

## **DG200-8EU Information**

Heisener.com

Manufacturer Curtis Industries

Part Number DG200-8EU

Category

Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description

AC/DC CONVERTER 15V 200W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DC200 OFTI	Cracifications
DCtZUU-8EU	<b>Specifications</b>

Manufacturer Part Number         DG200-8EU           Manufacturer         Curtis Industries           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         Tri-Mag, DG200           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         Tri-Mag, DG200           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer Part Number	DG200-8EU
Package         -           Series         Tri-Mag, DG200           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer	Curtis Industries
Package         -           Series         Tri-Mag, DG200           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         Tri-Mag, DG200           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Package	-
Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Series	Tri-Mag, DG200
Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         200W (300W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -20°C ~ 65°C (With Derating)           Features         PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Size / Dimension  15V  Output 2  - Current - Output 3  - Current - Output (Max)  12A  - Cumercial)  4kV (4000V)  6thic Derating 1  Features  PFC, Standby Output, Universal Input  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  PFC, Standby Output, Universal Input  Mounting Type  Size / Dimension  - Output 2  - Current - Output (Max)  - Current - Output	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output (Max)  - Chassis Mount	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max)  12A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -20°L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  200W (300W Forced Air)  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  12A  200W (300W Forced Air)  ITE (Commercial)  4kV (4000V)  6vitage - Isolation  4kV (4000V)  90%  Chassis Mount  5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  200W (300W Forced Air)  4kV (4000V)  Commercial)  4kV (4000V)  Fefficiency  90%  Chassis Mount  5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $4kV (4000V)$ Efficiency $90\%$ Operating Temperature $-20^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)FeaturesPFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension $5.00$ " L x $3.00$ " W x $1.42$ " H ( $127.0$ mm x $76.2$ mm x $36.1$ mm)	Current - Output (Max)	12A
Voltage - Isolation 4kV (4000V)  Efficiency 90%  Operating Temperature -20°C ~ 65°C (With Derating)  Features PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Power (Watts)	200W (300W Forced Air)
Efficiency 90%  Operating Temperature -20°C ~ 65°C (With Derating)  Features PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Applications	ITE (Commercial)
Operating Temperature  -20°C ~ 65°C (With Derating)  Features  PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Isolation	4kV (4000V)
Features PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Efficiency	90%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Operating Temperature	-20°C ~ 65°C (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Features	PFC, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)
•		Report errors?

### **DG200-8EU Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DG200-8EU Payment Methods**



















# **DG200-8EU Shipping Methods**













If you have any question about DG200-8EU, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com