



DG200M-GEC Information

Heisener.com

Part Number DG200M-GEC
Manufacturer Curtis Industries

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 28V 200W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DG200M-GEC Specifications

Manufacturer Curtis Industries Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer Part Number	DG200M-GEC	
AC DC Converters Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer	Curtis Industries	
Package - Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Tri-Mag, DG200 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Series	Tri-Mag, DG200	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Type	Enclosed	
Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.2A Power (Watts) 200W (300W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Petures PFC, Standby Output, Universal Input Mounting Type Size / Dimension - Output 2 - Chassis Mount - Current - Output (Max)	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Current - Output (Max) - Current - Output (Max	Voltage - Output 1	28V	
Voltage - Output 4 Current - Output (Max) 7.2A Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension -20°L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.2A 7.2A 7.2A 7.2A Power (Watts) 7.2A 7.2A 1.2A	Voltage - Output 3	-	
Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 200W (300W Forced Air) Medical 4kV (4000V) 90% Chypathage Chasting Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 4	-	
Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Current - Output (Max)	7.2A	
Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Power (Watts)	200W (300W Forced Air)	
Efficiency 90% Operating Temperature -20°C ~ 65°C (With Derating) Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Applications	Medical	
Operating Temperature -20°C ~ 65°C (With Derating) PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Isolation	4kV (4000V)	
Features PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Efficiency	90%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Operating Temperature	-20° C ~ 65° C (With Derating)	
Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Features	PFC, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	
		Repo	ort errors?

DG200M-GEC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DG200M-GEC Payment Methods



















DG200M-GEC Shipping Methods













If you have any question about DG200M-GEC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com