

DK1A-L2-3V Information



For Reference Only

Part Number DK1A-L2-3V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DK1A-L2-3V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package Series DK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole PC Pin		
CategoryRelaysPackage-SeriesDKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time8msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	DK1A-L2-3V
Package-SeriesDKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time8msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesDKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time8msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesDKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time8msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	DK
Coil Current 66.7mA Coil Voltage 3VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	3VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style 2.1 VDC	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time10msRelease Time8msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	2.1 VDC
Release Time 8ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
D	Termination Style	PC Pin
Report errors?		Report errors?

DK1A-L2-3V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DK1A-L2-3V Payment Methods


































If you have any question about DK1A-L2-3V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com