

# DL3-60RW6B

#### **DL3-60RW6B Information**

www.heisener.com	 DL3-60RW6B ITT Cannon, LLC Connectors, Interconnects Backplane Connectors - Specialized CONN 60POS ZIF PCB RCPT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **DL3-60RW6B** Specifications

Manufacturer Part NumberDL3-60RW6BManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackageBackplane Connectors - SpecializedPackage-SeriesDLConnector Usage-Connector StyleReceptacle, Hermaphroditic ContactsConnector Style-Number of Positions60Number of Rows6Number of Columns0.100"(2.54mm)Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessGoldCotorBlack	_		
CategoryConnectors, InterconnectsBackplane Connectors - SpecializedPackage-SeriesDLConnector Usage-Connector TypeReceptacle, Hernaphroditic ContactsConnector Style-Number of Positions60Number of Positions Loaded100° (2.54mm)Number of Rows6Number of Columns-Munther of Columns6Number of Columns-Solder-Contact Layout, Typical-FeaturesActuating Conschaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessGuin (2.7µm)Contact Finish ThicknessSolien (2.7µm)Contact Solien	Manufacturer Part Number	DL3-60RW6B	
AckageBackplane Connectors - SpecializedPackage-SeriesDLConnector Usage-Connector TypeReceptacle, Hermaphroditic ContactsConnector Style-Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Number of Columns-Number of StyleSolderContact Layout, Typical-FeaturesGoldContact Finish ThicknessSpin (1.27µm)ColorBlack	Manufacturer	ITT Cannon, LLC	
Package-SeriesDLConnector Usage-Connector TypeReceptacle, Hermaphroditic ContactsConnector Style-Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mumber of ColumnsSolderTerminationSolderContact Layout, Typical-FeaturesGoldContact Finish ThicknessSoljun (1.27µm)ColorBlack	Category	Connectors, Interconnects	
SeriesDLConnector Usage-Connector TypeReceptacle, Hermaphroditic ContactsConnector Style-Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mumber of Columns-Munting TypePanel MountContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishSoligerContact Finish ThicknessSpin (1.27µm)ColorBlack		Backplane Connectors - Specialized	
Connector Usage-Connector TypeReceptacle, Hernaphroditic ContactsConnector Style-Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishGuju (1.27µm)Contact FinishThicknessSpin (1.27µm)ColorBlack	Package	-	
Connector TypeReceptacle, Hermaphroditic ContactsConnector Style-Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessSoljuin (1.27µm)ColorBlack	Series	DL	
Connector Style-Number of Positions60Number of Positions LoadedAllPitch0.100° (2.54mm)Number of Rows6Number of Columns-Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishSoljin (1.27µm)Contact Finish ThicknessBlack	Connector Usage	-	
Number of Positions60Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishSoljari (1.27µm)Contact Finish ThicknessBlack	Connector Type	Receptacle, Hermaphroditic Contacts	
Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishGoldContact Finish ThicknessSoljin (1.27µm)ColorBlack	Connector Style	-	
Pitch0.100" (2.54mm)Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishSoljin (1.27µm)Contact Finish ThicknessBlack	Number of Positions	60	
Number of Rows6Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessSoljun (1.27µm)Contact Finish ThicknessBlack	Number of Positions Loaded	All	
Number of Columns-Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessGoldContact Finish ThicknessSpin (1.27µm)ColorBlack	Pitch	0.100" (2.54mm)	
Mounting TypePanel MountTerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact Finish ThicknessGoldContact Finish ThicknessSolpin (1.27µm)ColorBlack	Number of Rows	6	
TerminationSolderContact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishGoldContact Finish Thickness50µin (1.27µm)ColorBlack	Number of Columns	-	
Contact Layout, Typical-FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishGoldContact Finish Thickness50μin (1.27μm)ColorBlack	Mounting Type	Panel Mount	
FeaturesActuating Camshaft Socket, Zero Insertion Force (ZIF)Contact FinishGoldContact Finish Thickness50μin (1.27μm)ColorBlack	Termination	Solder	
Contact FinishGoldContact Finish Thickness50µin (1.27µm)ColorBlack	Contact Layout, Typical	-	
Contact Finish Thickness50µin (1.27µm)ColorBlack	Features	Actuating Camshaft Socket, Zero Insertion Force (ZIF)	
Color Black	Contact Finish	Gold	
	Contact Finish Thickness	50µin (1.27µm)	
Report errors?	Color	Black	
			Report errors?

#### **DL3-60RW6B** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **DL3-60RW6B** Payment Methods



### **DL3-60RW6B Shipping Methods**



If you have any question about DL3-60RW6B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com