



#### **DL60R24-43P9-6106 Information**

Heisener.com

Part Number DL60R24-43P9-6106

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 43POS FLANGE W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DL60R24-43P9-6106 Specifications

Manufacturer Part Number     DL60R24-43P9-6106       Manufacturer     TE Connectivity Deutsch Connectors       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-83723 Series III, DL       Connector Type     Receptacle, Male Pins       Number of Positions     43       Shell Size - Insert     24-43       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     9       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Nickel Plated, Electroless       Contact Finish     Gold       Features     -       Voltage - Rated     -       Current Rating     7.5A, 13A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-83723 Series III, DL Connector Type Receptacle, Male Pins Number of Positions 43 Shell Size - Insert 24-43 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation 9 Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Current Rating 7.5A, 13A	Manufacturer Part Number	DL60R24-43P9-6106
Package-SeriesMIL-DTL-83723 Series III, DLConnector TypeReceptacle, Male PinsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMIL-DTL-83723 Series III, DLConnector TypeReceptacle, Male PinsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-83723 Series III, DLConnector TypeReceptacle, Male PinsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A	Package	-
Number of Positions  Shell Size - Insert  24-43  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  9  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Features  -  Voltage - Rated  Current Rating  7.5A, 13A	Series	MIL-DTL-83723 Series III, DL
Shell Size - Insert24-43Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation 9 Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated Current Rating 7.5A, 13A	Number of Positions	43
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation9Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A, 13A	Shell Size - Insert	24-43
Termination Crimp Fastening Type Bayonet Lock Orientation 9 Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type  Orientation  9  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  -  7.5A, 13A	Mounting Type	Panel Mount, Flange
Orientation 9 Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Nickel Plated, Electroless  -  Cold  -  7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A, 13A	Orientation	9
Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated - Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated - Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	_
Report errors?	Current Rating	7.5A, 13A
T		Report errors?

#### **DL60R24-43P9-6106 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DL60R24-43P9-6106 Payment Methods



















### DL60R24-43P9-6106 Shipping Methods













If you have any question about DL60R24-43P9-6106, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com