



## **DLG100PS36 Information**



For Reference Only

Part Number DLG100PS36 Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC/CV AC/DC 36V 2.8A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DLG100PS36 Specifications**

Manufacturer Part Number         DLG100PS36           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         DLG           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         36V           Voltage - Output (Max)         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         DLG           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Manufacturer Part Number	DLG100PS36
Package         -           Series         DLG           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Manufacturer	XP Power
Package         -           Series         DLG           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         DLG           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)		LED Drivers
Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Package	-
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Series	DLG
Number of Outputs       1         Voltage - Input (Min)       90VAC         Voltage - Input (Max)       305VAC         Voltage - Output       36V         Current - Output (Max)       2.8A         Power (Watts)       100W         Voltage - Isolation       3.75kV (3750V)         Dimming       -         Features       OTP, OVP, SCP         Ratings       -         Operating Temperature       -30°C ~ 70°C         Efficiency       90%         Termination Style       Wire Leads         Size / Dimension       8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Туре	Constant Current, Voltage
Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         2.8A           Power (Watts)         100W           Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Topology	AC DC Converter
Voltage - Input (Max)       305VAC         Voltage - Output       36V         Current - Output (Max)       2.8A         Power (Watts)       100W         Voltage - Isolation       3.75kV (3750V)         Dimming       -         Features       OTP, OVP, SCP         Ratings       -         Operating Temperature       -30°C ~ 70°C         Efficiency       90%         Termination Style       Wire Leads         Size / Dimension       8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Number of Outputs	1
Voltage - Output       36V         Current - Output (Max)       2.8A         Power (Watts)       100W         Voltage - Isolation       3.75kV (3750V)         Dimming       -         Features       OTP, OVP, SCP         Ratings       -         Operating Temperature       -30°C ~ 70°C         Efficiency       90%         Termination Style       Wire Leads         Size / Dimension       8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Voltage - Input (Min)	90VAC
Current - Output (Max)       2.8A         Power (Watts)       100W         Voltage - Isolation       3.75kV (3750V)         Dimming       -         Features       OTP, OVP, SCP         Ratings       -         Operating Temperature       -30°C ~ 70°C         Efficiency       90%         Termination Style       Wire Leads         Size / Dimension       8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Voltage - Input (Max)	305VAC
Power (Watts)  100W  Voltage - Isolation 3.75kV (3750V)  Dimming - Features OTP, OVP, SCP  Ratings - Operating Temperature -30°C ~ 70°C  Efficiency 90%  Termination Style Size / Dimension  100W  3.75kV (3750V)  - OPP, OVP, SCP  - Wire Leads  8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Voltage - Output	36V
Voltage - Isolation         3.75kV (3750V)           Dimming         -           Features         OTP, OVP, SCP           Ratings         -           Operating Temperature         -30°C ~ 70°C           Efficiency         90%           Termination Style         Wire Leads           Size / Dimension         8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Current - Output (Max)	2.8A
Dimming - Features OTP, OVP, SCP  Ratings - Operating Temperature -30°C ~ 70°C  Efficiency 90%  Termination Style Wire Leads Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Power (Watts)	100W
Features OTP, OVP, SCP  Ratings - Operating Temperature -30°C ~ 70°C  Efficiency 90%  Termination Style Wire Leads  Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Voltage - Isolation	3.75kV (3750V)
Ratings - Operating Temperature -30°C ~ 70°C  Efficiency 90%  Termination Style Wire Leads  Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Dimming	-
Operating Temperature -30°C ~ 70°C  Efficiency 90%  Termination Style Wire Leads  Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Features	OTP, OVP, SCP
Efficiency 90%  Termination Style Wire Leads  Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Ratings	-
Termination Style Wire Leads Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Operating Temperature	-30°C ~ 70°C
Size / Dimension 8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)	Efficiency	90%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	8.74" L x 2.68" W x 1.54" H (222.0mm x 68.0mm x 39.0mm)
		Report errors?

### **DLG100PS36 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DLG100PS36 Payment Methods**


































If you have any question about DLG100PS36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com