

DLS2XP6AK44X

est a Quote

DLS2XP6AK44X Information

Heisener.com	Part Number	DLS2XP6AK44X	
	Manufacturer	Conec	Π
	Category	Connectors, Interconnects D-Sub Connectors	ğ
	Description	CONN D-SUB PLUG 15POS R/A SOLDER]
	Package	-	
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DLS2XP6AK44X Specifications

Manufacturer Conec Category Connectors, Interconnects D-Sub Connectors D-Sub Connectors Package - Series 0-Sub Connectors Connector Style D-Sub Connectors Connector Type D-Sub Number of Positions 15 Number of Rows 2 (DA, A) Contact Type Signal Mounting Type Board Edge, Through Hole, Right Angle Flange Feature Mating Side, Female Screwlock (4-40) Features Board Lock, Grounding Indents, Mounting Brackets Shell Material, Finish Steel Contact Finish Thickness - Contact Finish Thickness -		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeBoard Edge, Through Hole, Right AnglePlage FeatureMating Side, Female Screwlock (4-40)Flange FeatureSolderFeaturesGoldContact FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	DLS2XP6AK44X
D-Sub ConnectorsPackage-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Conec
Package-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeBoard Edge, Through Hole, Right AngleMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMoiting Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleMounting TypeSolderFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Series	-
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Board Edge, Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	-
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

DLS2XP6AK44X Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DLS2XP6AK44X Payment Methods



DLS2XP6AK44X Shipping Methods



If you have any question about DLS2XP6AK44X, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com