



DM7404N Information



For Reference Only

Part Number DM7404N

Manufacturer Fairchild/ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC INVERTER HEX 14 DIR

Description IC INVERTER HEX 14-DIP **Package** 14-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DM7404N Specifications

Manufacturer DM7404N Manufacturer Fairchild/ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-DIP (0.300", 7.62mm) Series 7400 Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low 400µA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 22ns @ 5V, 15pF Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)		
Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-DIP (0.300", 7.62mm) Series 7400 Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low 400μA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 22ns @ 5V, 15pF Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Manufacturer Part Number	DM7404N
Package 14-DIP (0.300", 7.62mm) Series 7400 Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low 400μA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 22ns @ 5V, 15pF Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Manufacturer	Fairchild/ON Semiconductor
Package 14-DIP (0.300", 7.62mm) Series 7400 Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low 400μA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 22ns @ 5V, 15pF Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Category	Integrated Circuits (ICs)
Series 7400 Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low 400μA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 22ns @ 5V, 15pF Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)		Logic - Gates and Inverters
Logic TypeInverterNumber of Circuits6Number of Inputs6Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 16mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Package	14-DIP (0.300", 7.62mm)
Number of Circuits6Number of Inputs6Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 16mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Series	7400
Number of Inputs6Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 16mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Logic Type	Inverter
Features Voltage - Supply 4.75 V ~ 5.25 V Current - Quiescent (Max) - Current - Output High, Low Logic Level - Low Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature O°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Number of Circuits	6
Voltage - Supply Current - Quiescent (Max) - Current - Output High, Low 400μA, 16mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature 0°C ~ 70°C Mounting Type Through Hole Supplier Device Package 14-DIP (0.300", 7.62mm)	Number of Inputs	6
Current - Quiescent (Max)-Current - Output High, Low400μA, 16mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Features	-
Current - Output High, Low $400\mu A, 16mA$ Logic Level - Low $0.8V$ Logic Level - High $2V$ Max Propagation Delay @ V, Max CL $22ns @ 5V, 15pF$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ Mounting Type $Through Hole$ Supplier Device Package 14 -PDIP Package / Case 14 -DIP $(0.300'', 7.62mm)$	Voltage - Supply	4.75 V ~ 5.25 V
Logic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Current - Quiescent (Max)	-
Logic Level - High2VMax Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Current - Output High, Low	400μA, 16mA
Max Propagation Delay @ V, Max CL22ns @ 5V, 15pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Logic Level - Low	0.8V
Operating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Logic Level - High	2V
Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Max Propagation Delay @ V, Max CL	22ns @ 5V, 15pF
Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Operating Temperature	0°C ~ 70°C
Package / Case 14-DIP (0.300", 7.62mm)	Mounting Type	Through Hole
	Supplier Device Package	14-PDIP
Report errors?	Package / Case	14-DIP (0.300", 7.62mm)
*		Report errors?

DM7404N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DM7404N Payment Methods


































If you have any question about DM7404N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com