



### **DM74LS10N Information**



For Reference Only

Part Number DM74LS10N

Manufacturer ON Semiconductor

Category Integrated Circuits (

Integrated Circuits (ICs)
Logic - Gates and Inverters

**Description** IC GATE NAND 3CH 3-INP 14DIP

**Package** 14-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **DM74LS10N Specifications**

Manufacturer         DM74LS10N           Manufacturer         ON Semiconductor           Category         Integrated Circuits (ICs)           Logic - Gates and Inverters           Package         14-DIP (0.300", 7.62mm)           Series         74LS           Logic Type         NAND Gate           Number of Circuits         3           Number of Inputs         3           Features         -           Voltage - Supply         4.75 V ~ 5.25 V           Current - Quiescent (Max)         -           Current - Output High, Low         400μA, 8mA           Logic Level - Low         0.8V           Logic Level - High         2V           Max Propagation Delay @ V, Max CL         15ns @ 5V, 50pF           Operating Temperature         0°C ~ 70°C           Mounting Type         Through Hole           Supplier Device Package         14-PDIP           Package / Case         14-DIP (0.300", 7.62mm)		
Category         Integrated Circuits (ICs)           Logic - Gates and Inverters           Package         14-DIP (0.300", 7.62mm)           Series         74LS           Logic Type         NAND Gate           Number of Circuits         3           Number of Inputs         3           Features         -           Voltage - Supply         4.75 V ~ 5.25 V           Current - Quiescent (Max)         -           Current - Output High, Low         400μA, 8mA           Logic Level - Low         0.8V           Logic Level - High         2V           Max Propagation Delay @ V, Max CL         15ns @ 5V, 50pF           Operating Temperature         0°C ~ 70°C           Mounting Type         Through Hole           Supplier Device Package         14-PDIP           Package / Case         14-DIP (0.300", 7.62mm)	Manufacturer Part Number	DM74LS10N
Package       14-DIP (0.300", 7.62mm)         Series       74LS         Logic Type       NAND Gate         Number of Circuits       3         Number of Inputs       3         Features       -         Voltage - Supply       4.75 V ~ 5.25 V         Current - Quiescent (Max)       -         Current - Output High, Low       400μA, 8mA         Logic Level - Low       0.8V         Logic Level - High       2V         Max Propagation Delay @ V, Max CL       15ns @ 5V, 50pF         Operating Temperature       0°C ~ 70°C         Mounting Type       Through Hole         Supplier Device Package       14-PDIP         Package / Case       14-DIP (0.300", 7.62mm)	Manufacturer	ON Semiconductor
Package       14-DIP (0.300", 7.62mm)         Series       74LS         Logic Type       NAND Gate         Number of Circuits       3         Number of Inputs       3         Features       -         Voltage - Supply       4.75 V ~ 5.25 V         Current - Quiescent (Max)       -         Current - Output High, Low       400μA, 8mA         Logic Level - Low       0.8V         Logic Level - High       2V         Max Propagation Delay @ V, Max CL       15ns @ 5V, 50pF         Operating Temperature       0°C ~ 70°C         Mounting Type       Through Hole         Supplier Device Package       14-PDIP         Package / Case       14-DIP (0.300", 7.62mm)	Category	Integrated Circuits (ICs)
Series74LSLogic TypeNAND GateNumber of Circuits3Number of Inputs3Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 8mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)		Logic - Gates and Inverters
Logic TypeNAND GateNumber of Circuits3Number of Inputs3Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 8mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Package	14-DIP (0.300", 7.62mm)
Number of Circuits3Number of Inputs3Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 8mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Series	74LS
Number of Inputs3Features-Voltage - Supply4.75 V ~ 5.25 VCurrent - Quiescent (Max)-Current - Output High, Low400μA, 8mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Logic Type	NAND Gate
Features - Current - Quiescent (Max) - Current - Output High, Low 400μA, 8mA  Logic Level - Low 0.8V  Logic Level - High 2V  Max Propagation Delay @ V, Max CL 15ns @ 5V, 50pF  Operating Temperature 0°C ~ 70°C  Mounting Type Through Hole  Supplier Device Package 14-PDIP  Package / Case 14.0DIP (0.300", 7.62mm)	Number of Circuits	3
Voltage - Supply  Current - Quiescent (Max)  - Current - Output High, Low  400μA, 8mA  Logic Level - Low  0.8V  Logic Level - High  2V  Max Propagation Delay @ V, Max CL  Operating Temperature  0°C ~ 70°C  Mounting Type  Through Hole  Supplier Device Package  14-DIP  Package / Case	Number of Inputs	3
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Features	-
Current - Output High, Low400μA, 8mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Voltage - Supply	4.75 V ~ 5.25 V
Logic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Current - Quiescent (Max)	-
Logic Level - High2VMax Propagation Delay @ V, Max CL15ns @ 5V, 50pFOperating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Current - Output High, Low	400μA, 8mA
Max Propagation Delay @ V, Max CL  Operating Temperature  O°C ~ 70°C  Mounting Type  Through Hole  Supplier Device Package  14-PDIP  Package / Case  14-DIP (0.300", 7.62mm)	Logic Level - Low	0.8V
Operating Temperature0°C ~ 70°CMounting TypeThrough HoleSupplier Device Package14-PDIPPackage / Case14-DIP (0.300", 7.62mm)	Logic Level - High	2V
Mounting Type Through Hole Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Max Propagation Delay @ V, Max CL	15ns @ 5V, 50pF
Supplier Device Package 14-PDIP Package / Case 14-DIP (0.300", 7.62mm)	Operating Temperature	0°C ~ 70°C
Package / Case 14-DIP (0.300", 7.62mm)	Mounting Type	Through Hole
	Supplier Device Package	14-PDIP
Report errors?	Package / Case	14-DIP (0.300", 7.62mm)
report direis.		Report errors?

#### **DM74LS10N Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DM74LS10N Payment Methods**



















### **DM74LS10N Shipping Methods**













If you have any question about DM74LS10N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com