



DMA9640M0R Information



For Reference Only

Part Number DMA9640M0R

Manufacturer Panasonic Electronic Components
Category Discrete Semiconductor Products

Transistors - Bipolar (BJT) - Arrays, Pre-Biased

Description TRANS PREBIAS DUAL PNP SSMINI6

Package SOT-563, SOT-666

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DMA9640M0R Specifications

Manufacturer Part NumberDMA9640M0RManufacturerPanasonic Electronic ComponentsCategoryDiscrete Semiconductor ProductsTransistors - Bipolar (BJT) - Arrays, Pre-BiasedPackageSOT-563, SOT-666Series-Transistor Type2 PNP - Pre-Biased (Dual)Current - Collector (Ic) (Max)100mAVoltage - Collector Emitter Breakdown (Max)50VResistor - Base (R1) (Ohms)2.2kResistor - Emitter Base (R2) (Ohms)47kDC Current Gain (hFE) (Min) @ Ic, Vce80 @ 5mA, 10VVce Saturation (Max) @ Ib, Ic250mV @ 500μA, 10mACurrent - Collector Cutoff (Max)500nAFrequency - Transition-Power - Max125mWMounting TypeSurface MountPackage / CaseSOT-563, SOT-666Supplier Device PackageSSMini6-F3-B	•	
Category Discrete Semiconductor Products Transistors - Bipolar (BJT) - Arrays, Pre-Biased Package SOT-563, SOT-666 Series - Transistor Type 2 PNP - Pre-Biased (Dual) Current - Collector (Ic) (Max) Voltage - Collector Emitter Breakdown (Max) SoV Resistor - Base (R1) (Ohms) Resistor - Emitter Base (R2) (Ohms) DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500µA, 10mA Current - Collector Cutoff (Max) Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Manufacturer Part Number	DMA9640M0R
Transistors - Bipolar (BJT) - Arrays, Pre-Biased Package SOT-563, SOT-666 Series - Transistor Type 2 PNP - Pre-Biased (Dual) Current - Collector (Ic) (Max) 100mA Voltage - Collector Emitter Breakdown (Max) 8 SoV Resistor - Base (R1) (Ohms) 2.2k Resistor - Emitter Base (R2) (Ohms) 47k DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500μA, 10mA Current - Collector Cutoff (Max) Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package	Manufacturer	Panasonic Electronic Components
Package SOT-563, SOT-666 Series - Transistor Type 2 PNP - Pre-Biased (Dual) Current - Collector (Ic) (Max) 100mA Voltage - Collector Emitter Breakdown (Max) 50V Resistor - Base (R1) (Ohms) 2.2k Resistor - Emitter Base (R2) (Ohms) 47k DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500µA, 10mA Current - Collector Cutoff (Max) 500nA Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Category	Discrete Semiconductor Products
Series - Transistor Type 2 PNP - Pre-Biased (Dual) Current - Collector (Ic) (Max) 100mA Voltage - Collector Emitter Breakdown (Max) 50V Resistor - Base (R1) (Ohms) 2.2k Resistor - Emitter Base (R2) (Ohms) 47k DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500µA, 10mA Current - Collector Cutoff (Max) 500nA Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B		Transistors - Bipolar (BJT) - Arrays, Pre-Biased
Transistor Type Current - Collector (Ic) (Max) Voltage - Collector Emitter Breakdown (Max) Resistor - Base (R1) (Ohms) Resistor - Emitter Base (R2) (Ohms) DC Current Gain (hFE) (Min) @ Ic, Vce Vce Saturation (Max) @ Ib, Ic Current - Collector Cutoff (Max) Frequency - Transition Power - Max Mounting Type Surface Mount Package / Case Supplier Device Package 2 PNP - Pre-Biased (Dual) 100mA 100mA 50V 2.2k 80 @ 5mA, 10V 2.50mV @ 500μA, 10mA 500nA 500nA Frequency - Transition - Surface Mount Surface Mount Sort-563, Sort-666 Supplier Device Package	Package	SOT-563, SOT-666
Current - Collector (Ic) (Max) Voltage - Collector Emitter Breakdown (Max) Resistor - Base (R1) (Ohms) 2.2k Resistor - Emitter Base (R2) (Ohms) DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic Current - Collector Cutoff (Max) Frequency - Transition - Power - Max Mounting Type Surface Mount Package / Case Supplier Device Package SSMini6-F3-B	Series	-
Voltage - Collector Emitter Breakdown (Max) Resistor - Base (R1) (Ohms) 2.2k Resistor - Emitter Base (R2) (Ohms) DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500µA, 10mA Current - Collector Cutoff (Max) Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Transistor Type	2 PNP - Pre-Biased (Dual)
Resistor - Base (R1) (Ohms) Resistor - Emitter Base (R2) (Ohms) DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic Current - Collector Cutoff (Max) Frequency - Transition Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package	Current - Collector (Ic) (Max)	100mA
Resistor - Emitter Base (R2) (Ohms)47kDC Current Gain (hFE) (Min) @ Ic, Vce80 @ 5mA, 10VVce Saturation (Max) @ Ib, Ic250mV @ 500μA, 10mACurrent - Collector Cutoff (Max)500nAFrequency - Transition-Power - Max125mWMounting TypeSurface MountPackage / CaseSOT-563, SOT-666Supplier Device PackageSSMini6-F3-B	Voltage - Collector Emitter Breakdown (Max)	50V
DC Current Gain (hFE) (Min) @ Ic, Vce 80 @ 5mA, 10V Vce Saturation (Max) @ Ib, Ic 250mV @ 500μA, 10mA Current - Collector Cutoff (Max) Frequency - Transition - Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Resistor - Base (R1) (Ohms)	2.2k
Vce Saturation (Max) @ Ib, Ic250mV @ 500μA, 10mACurrent - Collector Cutoff (Max)500nAFrequency - Transition-Power - Max125mWMounting TypeSurface MountPackage / CaseSOT-563, SOT-666Supplier Device PackageSSMini6-F3-B	Resistor - Emitter Base (R2) (Ohms)	47k
Current - Collector Cutoff (Max) Frequency - Transition Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	DC Current Gain (hFE) (Min) @ Ic, Vce	80 @ 5mA, 10V
Frequency - Transition Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Vce Saturation (Max) @ Ib, Ic	250mV @ 500μA, 10mA
Power - Max 125mW Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Current - Collector Cutoff (Max)	500nA
Mounting Type Surface Mount Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Frequency - Transition	-
Package / Case SOT-563, SOT-666 Supplier Device Package SSMini6-F3-B	Power - Max	125mW
Supplier Device Package SSMini6-F3-B	Mounting Type	Surface Mount
	Package / Case	SOT-563, SOT-666
Report errors?	Supplier Device Package	SSMini6-F3-B
		Report errors?

DMA9640M0R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DMA9640M0R Payment Methods





















DMA9640M0R Shipping Methods













If you have any question about DMA9640M0R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com