



#### **DMN3024LSS-13 Information**



For Reference Only

**Part Number** DMN3024LSS-13 **Manufacturer** Diodes Incorporated

Category Discrete Semiconductor Products
Transistors - FETs, MOSFETs - Single

**Description** MOSFET N-CH 30V 6.4A 8SO **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DMN3024LSS-13 Specifications**

Manufacturer Part Number         DMN3024LSS-13           Manufacturer         Diodes Incorporated           Category         Discrete Semiconductor Products           Transistors - FETs, MOSFETs - Single           Package         8-SOIC (0.154", 3.90mm Width)           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         30V           Current - Continuous Drain (Id) @ 25°C         6.4A (Ta)           Drive Voltage (Max Rds On, Min Rds On)         4.5V, 10V           Vgs(th) (Max) @ Id         3V @ 250µA           Gate Charge (Qg) (Max) @ Vgs         12.9nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         608pF @ 15V           Vgs (Max)         ±0V           FET Feature         -           Power Dissipation (Max)         1.6W (Ta)           Rds On (Max) @ Id, Vgs         24 mOhm @ 7A, 10V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         8-SO           Package / Case         8-SOIC (0.154", 3.90mm Width)		
Category         Discrete Semiconductor Products           Package         8-SOIC (0.154", 3.90mm Width)           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         30V           Current - Continuous Drain (Id) @ 25°C         6.4A (Ta)           Drive Voltage (Max Rds On, Min Rds On)         4.5V, 10V           Vgs(th) (Max) @ Id         3V @ 250µA           Gate Charge (Qg) (Max) @ Vgs         12.9n C @ 10V           Input Capacitance (Ciss) (Max) @ Vds         608pF @ 15V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         1.6W (Ta)           Rds On (Max) @ Id, Vgs         24 mOhm @ 7A, 10V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         8-SO           Package / Case         8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	DMN3024LSS-13
Package         8-SOIC (0.154", 3.90mm Width)           Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         30V           Current - Continuous Drain (Id) @ 25°C         6.4A (Ta)           Drive Voltage (Max Rds On, Min Rds On)         4.5V, 10V           Vgs(th) (Max) @ Id         3V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         12.9nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         608pF @ 15V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         1.6W (Ta)           Rds On (Max) @ Id, Vgs         24 mOhm @ 7A, 10V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         8-SO           Package / Case         8-SOIC (0.154", 3.90mm Width)	Manufacturer	Diodes Incorporated
Package8-SOIC (0.154", 3.90mm Width)Series-FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)30VCurrent - Continuous Drain (Id) @ 25°C6.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs12.9nC @ 10VInput Capacitance (Ciss) (Max) @ Vds608pF @ 15VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	Category	Discrete Semiconductor Products
Series         -           FET Type         N-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         30V           Current - Continuous Drain (Id) @ 25°C         6.4A (Ta)           Drive Voltage (Max Rds On, Min Rds On)         4.5V, 10V           Vgs(th) (Max) @ Id         3V @ 250μA           Gate Charge (Qg) (Max) @ Vgs         12.9nC @ 10V           Input Capacitance (Ciss) (Max) @ Vds         608pF @ 15V           Vgs (Max)         ±20V           FET Feature         -           Power Dissipation (Max)         1.6W (Ta)           Rds On (Max) @ Id, Vgs         24 mOhm @ 7A, 10V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         8-SO           Package / Case         8-SOIC (0.154", 3.90mm Width)		Transistors - FETs, MOSFETs - Single
FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)30VCurrent - Continuous Drain (Id) @ 25°C6.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs12.9nC @ 10VInput Capacitance (Ciss) (Max) @ Vds608pF @ 15VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	Package	8-SOIC (0.154", 3.90mm Width)
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)30VCurrent - Continuous Drain (Id) @ 25°C6.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs12.9nC @ 10VInput Capacitance (Ciss) (Max) @ Vds608pF @ 15VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	Series	-
Drain to Source Voltage (Vdss)30VCurrent - Continuous Drain (Id) @ 25°C6.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs12.9nC @ 10VInput Capacitance (Ciss) (Max) @ Vds608pF @ 15VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	FET Type	N-Channel
Current - Continuous Drain (Id) @ 25°C  Drive Voltage (Max Rds On, Min Rds On)  Vgs(th) (Max) @ Id  Gate Charge (Qg) (Max) @ Vgs  12.9nC @ 10V  Input Capacitance (Ciss) (Max) @ Vds  Vgs (Max)  **E20V  FET Feature  Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  1.6W (Ta)  24 mOhm @ 7A, 10V  Operating Temperature  Surface Mount  Supplier Device Package  Package / Case  6.4A (Ta)  6.4A (Ta)  6.4B (Ta)  6.4B (Ta)  4.5V, 10V  6.8pF @ 15V  4.5V  6.8pF @ 15V  4.5V  6.8pF @ 15V  6.8pp @ 10V  6.8pp @	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs12.9nC @ 10VInput Capacitance (Ciss) (Max) @ Vds608pF @ 15VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	Drain to Source Voltage (Vdss)	30V
Vgs(th) (Max) @ Id  Gate Charge (Qg) (Max) @ Vgs  12.9nC @ 10V  Input Capacitance (Ciss) (Max) @ Vds  608pF @ 15V  Vgs (Max)  FET Feature  - Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  24 mOhm @ 7A, 10V  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  Package / Case  8-SOIC (0.154", 3.90mm Width)	Current - Continuous Drain (Id) @ 25°C	6.4A (Ta)
Gate Charge (Qg) (Max) @ Vgs  Input Capacitance (Ciss) (Max) @ Vds  608pF @ 15V  Vgs (Max)  ±20V  FET Feature  - Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  24 mOhm @ 7A, 10V  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  8-SO  Package / Case  8-SOIC (0.154", 3.90mm Width)	Drive Voltage (Max Rds On, Min Rds On)	4.5V, 10V
Input Capacitance (Ciss) (Max) @ Vds  Vgs (Max)  ET Feature  Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  24 mOhm @ 7A, 10V  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  Package / Case  8-SOIC (0.154", 3.90mm Width)	Vgs(th) (Max) @ Id	3V @ 250μA
Vgs (Max)±20VFET Feature-Power Dissipation (Max)1.6W (Ta)Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	Gate Charge (Qg) (Max) @ Vgs	12.9nC @ 10V
FET Feature - Comparison (Max) 1.6W (Ta) 1.6W (Ta) 24 mOhm @ 7A, 10V Coperating Temperature -55°C ~ 150°C (TJ) Surface Mount Supplier Device Package 8-SO Package / Case 8-SOIC (0.154", 3.90mm Width)	Input Capacitance (Ciss) (Max) @ Vds	608pF @ 15V
Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  Package / Case  8-SOIC (0.154", 3.90mm Width)	Vgs (Max)	±20V
Rds On (Max) @ Id, Vgs24 mOhm @ 7A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPackage / Case8-SOIC (0.154", 3.90mm Width)	FET Feature	-
Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  8-SO  Package / Case  8-SOIC (0.154", 3.90mm Width)	Power Dissipation (Max)	1.6W (Ta)
Mounting Type Surface Mount Supplier Device Package 8-SO Package / Case 8-SOIC (0.154", 3.90mm Width)	Rds On (Max) @ Id, Vgs	24 mOhm @ 7A, 10V
Supplier Device Package 8-SO Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	-55°C ~ 150°C (TJ)
Package / Case 8-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Supplier Device Package	8-SO
Report errors?	Package / Case	8-SOIC (0.154", 3.90mm Width)
		Report errors?

### **DMN3024LSS-13 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DMN3024LSS-13 Payment Methods**





















### **DMN3024LSS-13 Shipping Methods**













If you have any question about DMN3024LSS-13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com