



DMN4034SSS-13 Information



For Reference Only

Part Number DMN4034SSS-13
Manufacturer Diodes Incorporated

Category Discrete Semiconductor Products
Transistors - FETs, MOSFETs - Single

Description MOSFET N-CH 40V 5.4A 8SO **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DMN4034SSS-13 Specifications

Manufacturer Part Number DMN4034SSS-13 Manufacturer Diodes Incorporated Category Discrete Semiconductor Products		
Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package 8-SOIC (0.154", 3.90mm Width) Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 40V Current - Continuous Drain (Id) @ 25°C 5.4A (Ta) Drive Voltage (Max Rds On, Min Rds On) 4.5V, 10V Vgs(th) (Max) @ Id 3V @ 250µA Gate Charge (Qg) (Max) @ Vgs 10nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 1.56W (Ta) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	DMN4034SSS-13
Package 8-SOIC (0.154", 3.90mm Width) Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 40V Current - Continuous Drain (Id) @ 25°C 5.4A (Ta) Drive Voltage (Max Rds On, Min Rds On) 4.5V, 10V Vgs(th) (Max) @ Id 3V @ 250μA Gate Charge (Qg) (Max) @ Vgs 10nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 1.56W (Ta) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer	Diodes Incorporated
Package8-SOIC (0.154", 3.90mm Width)Series-FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)40VCurrent - Continuous Drain (Id) @ 25°C5.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 10VInput Capacitance (Ciss) (Max) @ Vds453pF @ 20VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.56W (Ta)Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	Category	Discrete Semiconductor Products
Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 40V Current - Continuous Drain (Id) @ 25°C 5.4A (Ta) Drive Voltage (Max Rds On, Min Rds On) 4.5V, 10V Vgs(th) (Max) @ Id 3V @ 250μA Gate Charge (Qg) (Max) @ Vgs 10nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) 1.56W (Ta) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)		Transistors - FETs, MOSFETs - Single
FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 40V Current - Continuous Drain (Id) @ 25°C 5.4A (Ta) Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id 3V @ 250μA Gate Charge (Qg) (Max) @ Vgs 10nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package Package / Case 8-SOIC (0.154", 3.90mm Width)	Package	8-SOIC (0.154", 3.90mm Width)
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)40VCurrent - Continuous Drain (Id) @ 25°C5.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 10VInput Capacitance (Ciss) (Max) @ Vds453pF @ 20VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.56W (Ta)Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	Series	-
Drain to Source Voltage (Vdss)40VCurrent - Continuous Drain (Id) @ 25°C5.4A (Ta)Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 10VInput Capacitance (Ciss) (Max) @ Vds453pF @ 20VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.56W (Ta)Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	FET Type	N-Channel
Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) FET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs Operating Temperature Supplier Device Package Package / Case 5.4A (Ta) 6.4.5V, 10V 6.4.5V, 10V 6.4.7	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)4.5V, 10VVgs(th) (Max) @ Id3V @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 10VInput Capacitance (Ciss) (Max) @ Vds453pF @ 20VVgs (Max)±20VFET Feature-Power Dissipation (Max)1.56W (Ta)Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	Drain to Source Voltage (Vdss)	40V
Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Continuous Drain (Id) @ 25°C	5.4A (Ta)
Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package Package / Case 8-SOIC (0.154", 3.90mm Width)	Drive Voltage (Max Rds On, Min Rds On)	4.5V, 10V
Input Capacitance (Ciss) (Max) @ Vds 453pF @ 20V Vgs (Max) ±20V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Vgs(th) (Max) @ Id	3V @ 250μA
Vgs (Max)±20VFET Feature-Power Dissipation (Max)1.56W (Ta)Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	Gate Charge (Qg) (Max) @ Vgs	10nC @ 10V
FET Feature - 1.56W (Ta) Rds On (Max) @ Id, Vgs 34 mOhm @ 6A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Input Capacitance (Ciss) (Max) @ Vds	453pF @ 20V
Power Dissipation (Max) Rds On (Max) @ Id, Vgs Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package Package / Case 8-SOIC (0.154", 3.90mm Width)	Vgs (Max)	±20V
Rds On (Max) @ Id, Vgs34 mOhm @ 6A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package8-SOPPackage / Case8-SOIC (0.154", 3.90mm Width)	FET Feature	-
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Power Dissipation (Max)	1.56W (Ta)
Mounting Type Surface Mount Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Rds On (Max) @ Id, Vgs	34 mOhm @ 6A, 10V
Supplier Device Package 8-SOP Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	-55°C ~ 150°C (TJ)
Package / Case 8-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Supplier Device Package	8-SOP
Report errors?	Package / Case	8-SOIC (0.154", 3.90mm Width)
		Report errors?

DMN4034SSS-13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DMN4034SSS-13 Payment Methods





















DMN4034SSS-13 Shipping Methods













If you have any question about DMN4034SSS-13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com