



DMS050500-P5P-IC Information



For Reference Only

Part Number DMS050500-P5P-IC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 25W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DMS050500-P5P-IC Specifications

Manufacturer Part Number DMS050500-P5P-IC Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Manufacturer Part Number	DMS050500-P5P-IC
Package - Series - Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)5APower (Watts)25WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Series	-
Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 5A Power (Watts) No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 5A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Input Type	Multi-Blade (Included)
Current - Output (Max) 5A Power (Watts) 25W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 25W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Voltage - Output	5V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Current - Output (Max)	5A
Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Power (Watts)	25W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. \times 5.5mm O.D. \times 9.5mm Size / Dimension 4.24" L \times 2.27" W \times 1.32" H (107.7mm \times 57.7mm \times 33.5mm)	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Efficiency	70%
Size / Dimension 4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.24" L x 2.27" W x 1.32" H (107.7mm x 57.7mm x 33.5mm)
		Report errors?

DMS050500-P5P-IC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DMS050500-P5P-IC Payment Methods



















DMS050500-P5P-IC Shipping Methods













If you have any question about DMS050500-P5P-IC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com