

DP-101A-M-P Information



For Reference Only

Category

Manufacturer Panasonic Industrial Automation Sales

Sensors, Transducers

Part Number DP-101A-M-P

Pressure Sensors, Transducers

Description DIG PRSSR HGH M5 SHORT PORT PNP

Package Module Box with Display

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DP-101A-M-P Specifications

Manufacturer Part Number DP-101A-M-P Manufacturer Panasonic Industrial Automation Sales Category Sensors, Transducers Package Module Box with Display Series - Pressure Type Compound Operating Pressure ±14.5 PSI (±100 kPa) Output Type Analog Current/Voltage, PNP - Open Collector Output - Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package - **Report errors?*		
CategorySensors, TransducersPackageModule Box with DisplaySeries-Pressure TypeCompoundOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog Current/Voltage, PNP - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-	Manufacturer Part Number	DP-101A-M-P
Package Module Box with Display Series - Compound Operating Pressure Output Type Analog Current/Voltage, PNP - Open Collector Output Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure	Manufacturer	Panasonic Industrial Automation Sales
PackageModule Box with DisplaySeries-Pressure TypeCompoundOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog Current/Voltage, PNP - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-	Category	Sensors, Transducers
Series-Pressure TypeCompoundOperating Pressure±14.5 PSI (±100 kPa)Output TypeAnalog Current/Voltage, PNP - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Compound Operating Pressure ±14.5 PSI (±100 kPa) Output Type Analog Current/Voltage, PNP - Open Collector Output - Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Package	Module Box with Display
Operating Pressure ±14.5 PSI (±100 kPa) Output Type Analog Current/Voltage, PNP - Open Collector Output - Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Series	-
Output TypeAnalog Current/Voltage, PNP - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-	Pressure Type	Compound
Output Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Port Style Threaded Features - Termination Style Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature Package / Case Module Box with Display Supplier Device Package - - - - - - - - - - - - -	Operating Pressure	±14.5 PSI (±100 kPa)
Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-	Output Type	Analog Current/Voltage, PNP - Open Collector
Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleWire LeadsMaximum Pressure±72.52 PSI (±500 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with DisplaySupplier Device Package-	Output	-
Port Size Female - M5 Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Accuracy	-
Port Style Threaded Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Voltage - Supply	12 V ~ 24 V
Features - Termination Style Wire Leads Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Port Size	Female - M5
Termination Style Maximum Pressure ±72.52 PSI (±500 kPa) Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Port Style	Threaded
Maximum Pressure ± 72.52 PSI (± 500 kPa)Operating Temperature -10° C $\sim 50^{\circ}$ CPackage / CaseModule Box with DisplaySupplier Device Package-	Features	-
Operating Temperature -10°C ~ 50°C Package / Case Module Box with Display Supplier Device Package -	Termination Style	Wire Leads
Package / Case Module Box with Display Supplier Device Package -	Maximum Pressure	±72.52 PSI (±500 kPa)
Supplier Device Package -	Operating Temperature	-10°C ~ 50°C
	Package / Case	Module Box with Display
Report errors?	Supplier Device Package	-
		Report errors?

DP-101A-M-P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DP-101A-M-P Payment Methods



















DP-101A-M-P Shipping Methods













If you have any question about DP-101A-M-P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com