

DP-241-6-48

Request a Quote

DP-241-6-48 Information



For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DP-241-6-48 Specifications

Manufacturer Part NumberDP-241-6-48ManufacturerSignal TransformersCategoryTransformersPackage-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)630mACurrent - Output (Max)GalmaSecondary Winding(s)SingleConter TapYesPower - MaxSolder, Quick ConnectNouting TypeSolder, Quick ConnectSteir J Dimension82.60mm L x 44.30mm WHeight - Seated (Max)2500VrmsWeightSingleNotage - Solder Solder, Sold		
CategoryTansformersPackage-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)48VCurrent - Output (Max)G30mAPrimary Winding(s)DualSecondary Winding(s)SingleCurter TapYesPower - Max30 VAMounting TypeChassis MountSize / DimensionS260m L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 bs (499g)	Manufacturer Part Number	DP-241-6-48
InterfactPower TransformersPackage-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)48VCurrent - Output (Max)G30mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChasis MountSize / DimensionSloder, Quick ConnectSize / Dimension49.80mmHeight - Seated (Max)500VrmsWeight1.1 bs (499g)	Manufacturer	Signal Transformer
Package-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)48VCurrent - Output (Max)G30mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - MaxSolder, Quick ConnectMounting TypeSolder, Quick ConnectStez / DimensionSolder, Quick ConnectStez / Dimension49.80mmVoltage - Isolation2500VrmsWeight1.1 Ibs (499g)	Category	Transformers
Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)48VCurrent - Output (Max)G30mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChasis MountStez / DimensionSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation500VrmsWeight1.1 lbs (499g)		Power Transformers
TypeLaminated CoreYoltage - Primary115V, 230VVoltage - Secondary (Full Load)48VCurrent - Output (Max)630mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Package	-
Voltage - PrimaryInterventionVoltage - Secondary (Full Load)48VCurrent - Output (Max)630mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension49.80mmHeight - Seated (Max)2500VrmsWoitge - Isolation1.1 lbs (499g)	Series	241
Voltage - Secondary (Full Load)48VCurrent - Output (Max)630mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Туре	Laminated Core
Current - Output (Max)630mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsHeight1.1 lbs (499g)	Voltage - Secondary (Full Load)	48V
Secondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	630mA
Center TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Center Tap	Yes
Termination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Power - Max	30 VA
Size / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Mounting Type	Chassis Mount
Height - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Termination Style	Solder, Quick Connect
Voltage - Isolation2500VrmsWeight1.1 lbs (499g)	Size / Dimension	82.60mm L x 44.30mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	49.80mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

E-mail: salesdept@heisener.com

DP-241-6-48 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DP-241-6-48, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com