

DP-241-6-56

DP-241-6-56 Information



rer Signal Transformer Transformers Power Transformers XFRMR LAMINATED 30VA CHAS MOUNT -For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DP-241-6-56 Specifications

Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mA		
CategoryTansformersPackage-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountSize / DimensionSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)500VrmsVoltage - Isolation500VrmsWeight111bs (499g)	Manufacturer Part Number	DP-241-6-56
InterfactPower TransformersPackage-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChasis MountSize / DimensionSolder, Quick ConnectSize / Dimension49.80mmHeight - Seated (Max)2500VrmsWeight1.1 bs (499g)	Manufacturer	Signal Transformer
Package-Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChasis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm Lx 44.30mm WHeight - Seated (Max)920VrmsWotage - Isolation500VrmsWeight1.1 lbs (499g)	Category	Transformers
Series241TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeSolder, Quick ConnectSter/ Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation500VrmsWeight1.1 lbs (499g)		Power Transformers
TypeLaminated CoreTypeIafva CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - MaxGolvanMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Package	-
NypeInterformVoltage - Primary115V, 230VVoltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension49.80mmHeight - Seated (Max)49.80mmVoltage - Isolation1.1 lbs (499g)	Series	241
Voltage - Secondary (Full Load)56VCurrent - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Туре	Laminated Core
Current - Output (Max)540mAPrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Voltage - Secondary (Full Load)	56V
Secondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	540mA
Center TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Center Tap	Yes
Termination StyleSolder, Quick ConnectSize / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Power - Max	30 VA
Size / Dimension82.60mm L x 44.30mm WHeight - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Mounting Type	Chassis Mount
Height - Seated (Max)49.80mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Termination Style	Solder, Quick Connect
Voltage - Isolation2500VrmsWeight1.1 lbs (499g)	Size / Dimension	82.60mm L x 44.30mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	49.80mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

DP-241-6-56 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DP-241-6-56, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com