

DP150M-7S Information

Heisener.com

Manufact Category

Part Number DP150M-7S

Manufacturer Curtis Industries

Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description

AC/DC CONVERTER 12V 150W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DP150M-7S Specifications

Manufacturer Part Number DP150M-7S Manufacturer Curtis Industries Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DP150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DP150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer Part Number	DP150M-7S
Package - Series Tri-Mag, DP150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Manufacturer	Curtis Industries
Package - Series Tri-Mag, DP150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Tri-Mag, DP150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Package	-
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)150W (220W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency89%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Series	Tri-Mag, DP150
Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)150W (220W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency89%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Efficiency Operating Temperature PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 12V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation - Efficiency Operating Temperature PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension - Current - Output (Max) 12A - 150W (220W Forced Air) Medical - Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Efficiency Operating Temperature PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - Current - Output	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 150W (220W Forced Air) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 12A 150W (220W Forced Air) Medical - Chassis Mount - Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 3	-
Power (Watts) Applications Medical Voltage - Isolation - Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 150W (220W Forced Air) Medical -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Chassis Mount 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Output 4	-
Applications Medical Voltage - Isolation Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Current - Output (Max)	12A
Voltage - Isolation Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Power (Watts)	150W (220W Forced Air)
Efficiency 89% Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Applications	Medical
Operating Temperature -20°C ~ 70°C (With Derating) Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Voltage - Isolation	-
Features PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Efficiency	89%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Operating Temperature	-20°C ~ 70 °C (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)	Features	PFC, Remote Sense, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.42" H (127.0mm x 76.2mm x 36.1mm)
		Report errors?

DP150M-7S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DP150M-7S Payment Methods





















DP150M-7S Shipping Methods













If you have any question about DP150M-7S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com