

## **DP2-80-C5 Information**



For Reference Only

Part Number DP2-80-C5

Manufacturer Panasonic Industrial Automation Sales

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRESSURE -101.3KPA GAUGE

Package Module Box with Display

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **DP2-80-C5 Specifications**

Manufacturer Part NumberDP2-80-C5ManufacturerPanasonic Industrial Automation SalesCategorySensors, TransducersPackageModule Box with DisplaySeriesDP2Pressure TypeVacuumOperating Pressure-14.65 PSI (-101 kPa)Output TypeAnalog Voltage, NPN - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-71.07 PSI (-490 kPa)Operating Temperature-10°C ~ 50°CPackage / CaseModule Box with Display		
CategorySensors, TransducersPackageModule Box with DisplaySeriesDP2Pressure TypeVacuumOperating Pressure-14.65 PSI (-101 kPa)Output TypeAnalog Voltage, NPN - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-71.07 PSI (-490 kPa)Operating Temperature-10°C ~ 50°C	Manufacturer Part Number	DP2-80-C5
Package Module Box with Display Series DP2 Pressure Type Vacuum Operating Pressure -14.65 PSI (-101 kPa) Output Type Analog Voltage, NPN - Open Collector Output Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Connector Maximum Pressure -71.07 PSI (-490 kPa) Operating Pressure Series - Tormination Style -10°C ~ 50°C	Manufacturer	Panasonic Industrial Automation Sales
PackageModule Box with DisplaySeriesDP2Pressure TypeVacuumOperating Pressure-14.65 PSI (-101 kPa)Output TypeAnalog Voltage, NPN - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-71.07 PSI (-490 kPa)Operating Temperature-10°C ~ 50°C	Category	Sensors, Transducers
SeriesDP2Pressure TypeVacuumOperating Pressure-14.65 PSI (-101 kPa)Output TypeAnalog Voltage, NPN - Open CollectorOutput-Accuracy-Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-71.07 PSI (-490 kPa)Operating Temperature-10°C ~ 50°C		Pressure Sensors, Transducers
Pressure Type Vacuum Operating Pressure -14.65 PSI (-101 kPa) Output Type Analog Voltage, NPN - Open Collector Output Accuracy - Voltage - Supply 12 V ~ 24 V Port Size Female - M5 Port Style Threaded Features - Termination Style Connector  Maximum Pressure -71.07 PSI (-490 kPa) Operating Temperature -10.00 C ~ 50°C	Package	Module Box with Display
Operating Pressure Output Type Analog Voltage, NPN - Open Collector Output - Accuracy Voltage - Supply 12 V ~ 24 V  Port Size Female - M5  Port Style Threaded Features - Termination Style Connector Maximum Pressure Operating Temperature -10°C ~ 50°C	Series	DP2
Output Type Output - Accuracy - Voltage - Supply Port Size Port Style Features Termination Style Maximum Pressure Output - Analog Voltage, NPN - Open Collector - Connector Connector - Tormination Style Operating Temperature Analog Voltage, NPN - Open Collector - Connector - Connector - Tormination Style Connector - Tormination Style Connector - Tormination Style - Connector -	Pressure Type	Vacuum
Output - Accuracy - Voltage - Supply 12 V ~ 24 V  Port Size Female - M5  Port Style Threaded  Features - Termination Style Connector  Maximum Pressure -71.07 PSI (-490 kPa)  Operating Temperature -10°C ~ 50°C	Operating Pressure	-14.65 PSI (-101 kPa)
Accuracy  Voltage - Supply  12 V ~ 24 V  Port Size  Female - M5  Port Style  Threaded  Features  - Termination Style  Maximum Pressure  -71.07 PSI (-490 kPa)  Operating Temperature  -10°C ~ 50°C	Output Type	Analog Voltage, NPN - Open Collector
Voltage - Supply12 V ~ 24 VPort SizeFemale - M5Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-71.07 PSI (-490 kPa)Operating Temperature-10°C ~ 50°C	Output	-
Port Size Female - M5  Port Style Threaded  Features -  Termination Style Connector  Maximum Pressure -71.07 PSI (-490 kPa)  Operating Temperature -10°C ~ 50°C	Accuracy	-
Port Style Threaded  Features - Termination Style Connector  Maximum Pressure -71.07 PSI (-490 kPa) Operating Temperature -10°C ~ 50°C	Voltage - Supply	12 V ~ 24 V
Features - Termination Style Connector  Maximum Pressure -71.07 PSI (-490 kPa) Operating Temperature -10°C ~ 50°C	Port Size	Female - M5
Termination StyleConnectorMaximum Pressure $-71.07$ PSI $(-490 \text{ kPa})$ Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$	Port Style	Threaded
Maximum Pressure $-71.07 \text{ PSI } (-490 \text{ kPa})$ Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$	Features	-
Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$	Termination Style	Connector
	Maximum Pressure	-71.07 PSI (-490 kPa)
Package / Case Module Box with Display	Operating Temperature	-10°C ~ 50°C
	Package / Case	Module Box with Display
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

#### **DP2-80-C5 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DP2-80-C5 Payment Methods**





















### **DP2-80-C5 Shipping Methods**













If you have any question about DP2-80-C5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com