

DP241-6-16A33 Information

Heisener.com

Part Number DP241-6-16A33

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 30VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DP241-6-16A33 Specifications

Manufacturer Part NumberDP241-6-16A33ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)16VCurrent - Output (Max)2APrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)		
CategoryTransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)16VCurrent - Output (Max)2APrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Manufacturer Part Number	DP241-6-16A33
Package Power Transformers Package Chassis-Tran Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) 16V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Size / Dimension Weight Secondary Secondary Secondary Secondary Secondary Secondary Size / Dimension Solder, Quick Connect Size / Solder, Quick Con	Manufacturer	Pulse Electronics Power
Package - Series Chassis-Tran Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) 16V Current - Output (Max) 2A Primary Winding(s) Dual Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Category	Transformers
SeriesChassis-TranTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)16VCurrent - Output (Max)2APrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) 16V Current - Output (Max) 2A Primary Winding(s) Dual Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 16V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight	Series	Chassis-Tran
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Reight - Seated (Max) Voltage - Isolation Yes 16V 2A 16V 2A 108 108 108 108 108 108 24 25 108 108 108 108 108 108 108 10	Туре	Laminated Core
Current - Output (Max)2APrimary Winding(s)DualSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual Single Yes Yes Chassis Mount Chassis Mount Solder, Quick Connect 82.55mm L x 49.28mm W 42.93mm Voltage - Isolation 2500Vrms 1.1 lbs (499g)	Voltage - Secondary (Full Load)	16V
Secondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	2A
Center TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Secondary Winding(s)	Single
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Center Tap	Yes
Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	30 VA
Size / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Mounting Type	Chassis Mount
Height - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Termination Style	Solder, Quick Connect
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	82.55mm L x 49.28mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	42.93mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

DP241-6-16A33 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DP241-6-16A33 Payment Methods





















DP241-6-16A33 Shipping Methods













If you have any question about DP241-6-16A33, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com