



DPA090060-S/T-TK Information

Heisener.com

Part Number DPA090060-S/T-TK

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 9V 5W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPA090060-S/T-TK Specifications

| Manufacturer Part Number DPA090060-S/T-TK Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series - Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals ERport errors? | | |
|--|---------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series - Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Manufacturer Part Number | DPA090060-S/T-TK |
| Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output9VACCurrent - Output (Max)600mAPower (Watts)5WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorStripped, Tinned Wire LeadsSize / Dimension1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm)ApprovalscUL | Manufacturer | CUI Inc. |
| Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output9VACCurrent - Output (Max)600mAPower (Watts)5WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorStripped, Tinned Wire LeadsSize / Dimension1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm)ApprovalscUL | Category | Power Supplies - External/Internal (Off-Board) |
| Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output9VACCurrent - Output (Max)600mAPower (Watts)5WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorStripped, Tinned Wire LeadsSize / Dimension1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm)ApprovalscUL | | AC AC Wall Adapters |
| Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals | Package | - |
| Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Series | - |
| Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Region Utilized | North America |
| Voltage - Input Voltage - Output 9VAC Current - Output (Max) 600mA Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) cUL | Form | Wall Mount (Class II) |
| Voltage - Output (Max) 9VAC Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Input Type | Fixed Blade |
| Current - Output (Max) 600mA Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Voltage - Input | 120VAC |
| Power (Watts) 5W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Voltage - Output | 9VAC |
| No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Current - Output (Max) | 600mA |
| Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Power (Watts) | 5W |
| Efficiency - Operating Temperature - Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | No Load Power Consumption | - |
| Operating Temperature Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Applications | ITE (Commercial) |
| Output Connector Stripped, Tinned Wire Leads Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Efficiency | - |
| Size / Dimension 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) Approvals cUL | Operating Temperature | - |
| Approvals cUL | Output Connector | Stripped, Tinned Wire Leads |
| | Size / Dimension | 1.56" L x 1.77" W x 2.32" H (39.5mm x 45.0mm x 59.0mm) |
| Report errors? | Approvals | cUL |
| | | Report errors? |

DPA090060-S/T-TK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPA090060-S/T-TK Payment Methods





















DPA090060-S/T-TK Shipping Methods













If you have any question about DPA090060-S/T-TK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com