



DPA120060-P14/R Information

Heisener.com

Part Number DPA120060-P14/R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 12V 7W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPA120060-P14/R Specifications

Manufacturer Part Number DPA120060-P14/R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series - Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 600mA Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -		
CategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)600mAPower (Watts)7WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mmSize / Dimension-Approvals-	Manufacturer Part Number	DPA120060-P14/R
Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)600mAPower (Watts)7WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mmSize / Dimension-Approvals-	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)600mAPower (Watts)7WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mmSize / Dimension-Approvals-	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)600mAPower (Watts)7WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mmSize / Dimension-Approvals-		AC AC Wall Adapters
Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)600mAPower (Watts)7WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mmSize / Dimension-Approvals-	Package	-
Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 600mA Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 600mA Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 600mA Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension Approvals	Form	Wall Mount (Class II)
Voltage - Output (Max) 600mA Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Input Type	Fixed Blade
Current - Output (Max) 600mA Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Voltage - Input	120VAC
Power (Watts) 7W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Voltage - Output	12VAC
No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Current - Output (Max)	600mA
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Power (Watts)	7W
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	No Load Power Consumption	-
Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm Size / Dimension - Approvals -	Efficiency	-
Size / Dimension - Approvals -	Operating Temperature	-
Approvals -	Output Connector	Barrel Plug R/A, 1.7mm I.D. x 4.75mm O.D. x 9.5mm
	Size / Dimension	-
D	Approvals	-
Report errors?		Report errors?

DPA120060-P14/R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPA120060-P14/R Payment Methods



















DPA120060-P14/R Shipping Methods













If you have any question about DPA120060-P14/R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com