



DPA120100-P12/R Information

Heisener.com

Part Number DPA120100-P12/R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 12V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPA120100-P12/R Specifications

Manufacturer Part NumberDPA120100-P12/RManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output (Max)1APower (Watts)12WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mmSize / Dimension-		
CategoryPower Supplies - External/Internal (Off-Board)Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1APower (Watts)12WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mmSize / Dimension-Approvals-	Manufacturer Part Number	DPA120100-P12/R
Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1APower (Watts)12WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mmSize / Dimension-Approvals-	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1APower (Watts)12WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mmSize / Dimension-Approvals-	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1APower (Watts)12WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mmSize / Dimension-Approvals-		AC AC Wall Adapters
Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	Package	-
Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals -	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals -	Form	Wall Mount (Class II)
Voltage - Output Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals - Output Connector	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals -	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals -	Voltage - Output	12VAC
No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension Approvals -	Current - Output (Max)	1A
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	Power (Watts)	12W
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	No Load Power Consumption	-
Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm Size / Dimension - Approvals -	Efficiency	-
Size / Dimension - Approvals -	Operating Temperature	-
Approvals -	Output Connector	Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm
	Size / Dimension	-
Perpert errors?	Approvals	-
Report chois:		Report errors?

DPA120100-P12/R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPA120100-P12/R Payment Methods

































If you have any question about DPA120100-P12/R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com