



DPA120200-P1P Information



For Reference Only

Part Number DPA120200-P1P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 12V 2W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPA120200-P1P Specifications

Manufacturer Part Number DPA120200-PIP Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output (Max) 200mA Power (Watts) 2W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -		
CategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)200mAPower (Watts)2WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.5mmSize / Dimension-Approvals-	Manufacturer Part Number	DPA120200-P1P
Package - Series - North America - North America - Series Input Type Fixed Blade - Series Input Input Type Input I	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)200mAPower (Watts)2WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.5mmSize / Dimension-Approvals-	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)200mAPower (Watts)2WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.5mmSize / Dimension-Approvals-		AC AC Wall Adapters
Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)200mAPower (Watts)2WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.5mmSize / Dimension-Approvals-	Package	-
Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 200mA Power (Watts) 2W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 200mA Power (Watts) 2W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension Approvals	Form	Wall Mount (Class II)
Voltage - Output Current - Output (Max) 200mA Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Size / Dimension Approvals 12VAC 200mA 12W Commandary - Commandary	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension Approvals -	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Applications Efficiency Operating Temperature Output Connector Size / Dimension Approvals 2W Commercial	Voltage - Output	12VAC
No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Current - Output (Max)	200mA
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Power (Watts)	2W
Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	No Load Power Consumption	-
Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Applications	ITE (Commercial)
Output Connector Phono Plug, 3.5mm O.D. x 14.5mm Size / Dimension - Approvals -	Efficiency	-
Size / Dimension - Approvals -	Operating Temperature	-
Approvals -	Output Connector	Phono Plug, 3.5mm O.D. x 14.5mm
	Size / Dimension	-
Report errors?	Approvals	-
		Report errors?

DPA120200-P1P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPA120200-P1P Payment Methods



















DPA120200-P1P Shipping Methods













If you have any question about DPA120200-P1P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com