

### **DPC-10-2400 Information**

Heisener.com

Part NumberDPC-10-2400ManufacturerSignal TransformerCategoryTransformers

Power Transformers

**Description** XFRMR LAMINATED 24VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DPC-10-2400 Specifications**

Manufacturer Part NumberDPC-10-2400ManufacturerSignal TransformerCategoryTransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 57.20mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)		
Category         Transformers           Package         -           Series         DPC           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 5V, Series 10V           Current - Output (Max)         Parallel 4.8A, Series 2.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         24 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.30mm L x 57.20mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         1500Vrms           Weight         0.75 lb (340.19g)	Manufacturer Part Number	DPC-10-2400
Package Power Transformers  Package Porc Series DPC  Type Laminated Core Voltage - Primary I15V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Abouting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation Power Transformers  Power Transformers  Power Transformers  Power Transformers  Por Pin  115V, 230V Parallel 5V, Series 10V Parallel 4.8A, Series 2.4A Primary Winding(s)  Dual Poul  Poul  15V - 20V Poul  15V - 230V Poul  15V - 240V Poul  15V - 240V Poul  15V - 240V Poul  15V - 240V Poul  15V	Manufacturer	Signal Transformer
Package         -           Series         DPC           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 5V, Series 10V           Current - Output (Max)         Parallel 4.8A, Series 2.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         24 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.30mm L x 57.20mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         1500Vrms           Weight         0.75 lb (340.19g)	Category	Transformers
SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 57.20mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 5V, Series 10V  Current - Output (Max) Parallel 4.8A, Series 2.4A  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 24 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.30mm L x 57.20mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 5V, Series 10V  Current - Output (Max)  Parallel 4.8A, Series 2.4A  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Additional Style  Through Hole  Termination Style  PC Pin  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  115V, 230V  Parallel 5V, Series 10V  Parallel 4.8A, Series 2.4A  Primary Winding (s)  Dual  Secondary Winding (s)  Dual  Secondary Winding (s)  Dual  Secondary Winding (s)  Parallel 4.8A, Series 2.4A  Primary Winding (s)  Dual  Secondary Win	Series	DPC
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 5V, Series 10V  Parallel 4.8A, Series 2.4A  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  Parallel 5V, Series 10V  Parallel 4.8A, Series 2.4A  Dual  Secondary Winding(s)  104  105  105  105  105  105  105  105	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 4.8A, Series 2.4A Primary Winding(s) Dual No Powal No No Powal No	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  August Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  Dual  No  100  100  100  100  100  100  100	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 57.20mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Current - Output (Max)	Parallel 4.8A, Series 2.4A
Center Tap No  Power - Max 24 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.30mm L x 57.20mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.30mm L x 57.20mm W  Height - Seated (Max)  Voltage - Isolation  1500Vrms  Weight  0.75 lb (340.19g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.30mm L x 57.20mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.30mm L x 57.20mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Power - Max	24 VA
Size / Dimension 41.30mm L x 57.20mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Seated (Max)  1500Vrms  0.75 lb (340.19g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Size / Dimension	41.30mm L x 57.20mm W
Weight 0.75 lb (340.19g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.75 lb (340.19g)
		Report errors?

#### **DPC-10-2400 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **DPC-10-2400 Payment Methods**



















## **DPC-10-2400 Shipping Methods**













If you have any question about DPC-10-2400, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com