

DPC-10-440 Information

Heisener.com

Part Number DPC-10-440

Manufacturer Signal Transformer

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 4.4VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPC-10-440 Specifications

Manufacturer Part NumberDPC-10-440ManufacturerSignal TransformerCategoryTransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 880mA, Series 440mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)		
Category Transformers Power Transformers Package - Series DPC Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Manufacturer Part Number	DPC-10-440
Power Transformers Package - Series DPC Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Manufacturer	Signal Transformer
Package - Series DPC Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight	Category	Transformers
Series DPC Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) Voltage - Isolation Weight 115V, 230V Parallel 880mA, Series 440mA Puallel 880mA, Series 10V Aloma 440mA 1500Vrms Voltage - Isolation O .313 lb (141.97g)	Series	DPC
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 880mA, Series 440mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 5V, Series 440mA Primary Winding (s) Dual Secondary Winding (s) Dual Secondary Winding (s) Dual No 14.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) Voltage - Isolation 0.313 lb (141.97g)	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 880mA, Series 440mA Dual Pull Pull Pull Power - 440mA No Power - 440	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Dual No 1500Vrms Dual No 1500Vrms 0.313 lb (141.97g)	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Current - Output (Max)	Parallel 880mA, Series 440mA
Center Tap No Power - Max 4.4 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Power - Max	4.4 VA
Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Size / Dimension	41.30mm L x 31.80mm W
Weight 0.313 lb (141.97g)	Height - Seated (Max)	34.92mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.313 lb (141.97g)
		Report errors?

DPC-10-440 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPC-10-440 Payment Methods



















DPC-10-440 Shipping Methods













If you have any question about DPC-10-440, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com